

Package ‘buildmer’

August 26, 2020

Title Stepwise Elimination and Term Reordering for Mixed-Effects Regression

Version 1.7.1

Description Finds the largest possible regression model that will still converge for various types of regression analyses (including mixed models and generalized additive models) and then optionally performs stepwise elimination similar to the forward and backward effect-selection methods in SAS, based on the change in log-likelihood or its significance, Akaike's Information Criterion, the Bayesian Information Criterion, the explained deviance, or the F-test of the change in R^2 .

Depends R (>= 3.2)

Imports graphics, lme4, methods, mgcv, nlme, plyr, stats, utils

Suggests GLMMadaptive, MASS, gamm4, glmertree, glmmTMB, knitr, lmerTest, nnet, ordinal, parallel, partykit, pbkrtest, rmarkdown

License FreeBSD

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

BugReports <https://github.com/cvoeten/buildmer/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Cesko C. Voeten [aut, cre] (<<https://orcid.org/0000-0003-4687-9973>>)

Maintainer Cesko C. Voeten <cvoeten@gmail.com>

Repository CRAN

Date/Publication 2020-08-26 05:40:03 UTC

R topics documented:

buildmer-package	2
add.terms	3

build.formula	3
buildbam	4
buildclmm	5
buildcustom	6
buildgam	8
buildgamm	9
buildgamm4	10
buildGLMMadaptive	11
buildglmmTMB	12
buildgls	13
buildlme	14
buildmer	15
buildmer-class	16
buildmerControl	17
buildmertree	20
buildmultinom	21
conv	22
converged	23
diag.formula-method	24
migrant	24
re2mgcv	25
remove.terms	25
tabulate.formula	26
vowels	27
Index	28

buildmer-package	<i>Construct and fit as complete a model as possible and perform step-wise elimination</i>
------------------	--

Description

The `buildmer` package consists of a number of functions, each designed to fit specific types of models (e.g. `buildmer` for mixed-effects regression, `buildgam` for generalized additive models, `buildmertree` for mixed-effects-regression trees, and so forth). The common parameters shared by all (or most of) these functions are documented here. If you are looking for a more general description of what the various `build...` functions do, see under ‘Details’. For function-specific details, see the documentation for each individual function.

add.terms	<i>Add terms to a formula</i>
-----------	-------------------------------

Description

Add terms to a formula

Usage

```
add.terms(formula, add)
```

Arguments

formula	The formula to add terms to.
add	A vector of terms to add. To add terms nested in random-effect groups, use ‘(term group)’ syntax if you want to add an independent random effect (e.g. ‘(olderterm group) + (term group)’), or use ‘term group’ syntax if you want to add a dependent random effect to a pre-existing term group (if no such group exists, it will be created at the end of the formula).

Value

The updated formula.

Examples

```
library(buildmer)
form <- Reaction ~ Days + (1|Subject)
add.terms(form, 'Days|Subject')
add.terms(form, '(0+Days|Subject)')
add.terms(form, c('many', 'more|terms', 'to|terms', '(be|added)', 'to|test'))
```

build.formula	<i>Convert a buildmer term list into a proper model formula</i>
---------------	---

Description

Convert a buildmer term list into a proper model formula

Usage

```
build.formula(dep, terms, env = parent.frame())
```

Arguments

dep	The dependent variable.
terms	The term list.
env	The environment of the formula to return.

Value

A formula.

Examples

```
library(buildmer)
form1 <- Reaction ~ Days + (Days|Subject)
terms <- tabulate.formula(form1)
form2 <- build.formula(dep='Reaction', terms)

# check that the two formulas give the same results
library(lme4)
check <- function (f) resid(lmer(f, sleepstudy))
all.equal(check(form1), check(form2))
```

buildbam	<i>Use buildmer to fit big generalized additive models using bam from package mgcv</i>
----------	--

Description

Use buildmer to fit big generalized additive models using bam from package mgcv

Usage

```
buildbam(
  formula,
  data = NULL,
  family = gaussian(),
  buildmerControl = buildmerControl(),
  ...
)
```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl

... Additional options to be passed to bam; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

To work around an issue in bam(), you must make sure that your data do not contain a variable named 'intercept'.

lme4 random effects are supported: they will be automatically converted using [re2mgcv](#).

As bam uses PQL, only crit='deviance' is supported for non-Gaussian errors.

See Also

[buildmer-package](#)

Examples

```
library(buildmer)
model <- buildbam(f1 ~ s(timepoint,by=following) + s(participant,by=following,bs='re') +
  s(participant,timepoint,by=following,bs='fs'),data=vowels)
```

buildclmm	<i>Use buildmer to fit cumulative link mixed models using clmm from package ordinal</i>
-----------	---

Description

Use buildmer to fit cumulative link mixed models using clmm from package ordinal

Usage

```
buildclmm(formula, data = NULL, buildmerControl = buildmerControl(), ...)
```

Arguments

formula	A formula specifying both fixed and random effects using lme4 syntax
data	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to clmm; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

buildclmm tries to guess which of ... are intended for clm and which are for clmm. If this goes wrong, this behavior can be suppressed by passing explicit clm.control and clmm.control arguments. If one of these is specified, any control argument is interpreted to be intended for the other one; if both are specified in conjunction with a third control argument, an error is raised.

See Also

[buildmer-package](#)

Examples

```
if (requireNamespace('ordinal')) {
  model <- buildclmm(SURENESS ~ PROD + (1|RESP), data=ordinal::soup, link='probit',
  threshold='equidistant')
}
```

buildcustom	<i>Use buildmer to perform stepwise elimination using a custom fitting function</i>
-------------	---

Description

Use buildmer to perform stepwise elimination using a custom fitting function

Usage

```
buildcustom(
  formula,
  data = NULL,
  fit = function(p, formula) stop("'fit' not specified"),
  crit = function(p, ref, alt) stop("'crit' not specified"),
  elim = function(x) stop("'elim' not specified"),
  REML = FALSE,
  buildmerControl = buildmerControl(),
  ...
)
```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
fit	A function taking two arguments, of which the first is the buildmer parameter list p and the second one is a formula. The function must return a single object, which is treated as a model object fitted via the provided formula. The function must return an error ('stop()') if the model does not converge

<code>crit</code>	A function taking one argument and returning a single value. The argument is the return value of the function passed in <code>fit</code> , and the returned value must be a numeric indicating the goodness of fit, where smaller is better (like AIC or BIC).
<code>elim</code>	A function taking one argument and returning a single value. The argument is the return value of the function passed in <code>crit</code> , and the returned value must be a logical indicating if the small model must be selected (return <code>TRUE</code>) or the large model (return <code>FALSE</code>)
<code>REML</code>	A logical indicating if the fitting function wishes to distinguish between fits differing in fixed effects (for which <code>p\$reml</code> will be set to <code>FALSE</code>) and fits differing only in the random part (for which <code>p\$reml</code> will be <code>TRUE</code>). Note that this ignores the usual semantics of <code>buildmer</code> 's optional <code>REML</code> argument, because they are redundant: if you wish to force <code>REML</code> on or off, simply code it so in your custom fitting function.
<code>buildmerControl</code>	Control arguments for <code>buildmer</code> — see the general documentation under buildmerControl
<code>...</code>	Additional options to be passed to the fitting function, such as perhaps a data argument; for backward-compatibility reasons, will also accept <code>buildmer</code> control parameters, although those specified in <code>buildmerControl</code> will take precedence

See Also

[buildmer-package](#)

Examples

```
## Use \code{buildmer} to do stepwise linear discriminant analysis
library(buildmer)
migrant[, -1] <- scale(migrant[, -1])
flipfit <- function (p, formula) {
  # The predictors must be entered as dependent variables in a MANOVA
  # (i.e. the predictors must be flipped with the dependent variable)
  Y <- model.matrix(formula, migrant)
  m <- lm(Y ~ 0+migrant$changed)
  # the model may error out when asking for the MANOVA
  test <- try(anova(m))
  if (inherits(test, 'try-error')) test else m
}
crit.F <- function (p, a, b) { # use whole-model F
  pvals <- anova(b)$'Pr(>F)' # not valid for backward!
  pvals[length(pvals)-1]
}
crit.Wilks <- function (p, a, b) {
  if (is.null(a)) return(crit.F(p, a, b)) #not completely correct, but close as F approximates X2
  Lambda <- anova(b, test='Wilks')$Wilks[1]
  p <- length(coef(b))
  n <- 1
  m <- nrow(migrant)
  Bartlett <- ((p-n+1)/2-m)*log(Lambda)
  pchisq(Bartlett, n*p, lower.tail=FALSE)
```

```

}

# First, order the terms based on Wilks' Lambda
model <- buildcustom(changed ~ friends.nl+friends.be+multilingual+standard+hearing+reading+
  attention+sleep+gender+handedness+diglossic+age+years,direction='order',fit=flipfit,
  crit=crit.Wilks)
# Now, use the six most important terms (arbitrary choice) in the LDA
if (require('MASS')) model <- lda(changed ~ diglossic + age + reading + friends.be + years +
  multilingual,data=migrant)

```

buildgam	<i>Use buildmer to fit generalized additive models using gam from package mgcv</i>
----------	--

Description

Use buildmer to fit generalized additive models using gam from package mgcv

Usage

```

buildgam(
  formula,
  data = NULL,
  family = gaussian(),
  quickstart = 0,
  buildmerControl = buildmerControl(),
  ...
)

```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
quickstart	A numeric with values from 0 to 5. If set to 1, will use bam to obtain starting values for gam's outer iteration, potentially resulting in a much faster fit for each model. If set to 2, will disregard ML/REML and always use bam's fREML for the quickstart fit. 3 also sets discrete=TRUE. Values between 3 and 4 fit the quickstart model to a subset of that value (e.g. quickstart=3.1 fits the quickstart model to 10% of the data, which is also the default if quickstart=3. Values between 4 and 5 do the same, but also set a very sloppy convergence tolerance of 0.2.
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to gam; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

To work around an issue in `gam()`, you must make sure that your data do not contain a variable named 'intercept'.

lme4 random effects are supported: they will be automatically converted using [re2mgcv](#).

If `gam`'s optimizer argument is not set to use outer iteration, `gam` fits using PQL. In this scenario, only `crit='deviance'` is supported.

General families implemented in `mgcv` are supported, provided that they use normal formulas. Currently, this is only true of the `cox.ph` family. Because this family can only be fitted using REML, `buildgam` automatically sets `gam`'s `select` argument to `TRUE` and prevents removal of parametric terms.

The quickstart function is experimental. If you desire more control (e.g. `discrete=FALSE` but `use.chol=TRUE`), additional options can be provided as extra arguments and will be passed on to `bam` as they are applicable. Note that `quickstart` needs to be larger than 0 to trigger the quickstart path at all.

If scaled-t errors are used (`family=scat`), the quickstart path will also provide initial values for the two theta parameters (corresponding to the degrees of freedom and the scale parameter), but only if your installation of package `mgcv` is at least at version 1.8-32.

See Also

[buildmer-package](#)

Examples

```
library(buildmer)
model <- buildgam(f1 ~ s(timepoint,by=following) + s(participant,by=following,bs='re') +
  s(participant,timepoint,by=following,bs='fs'),data=vowels)
```

buildgamm

Use buildmer to fit big generalized additive models using gamm from package mgcv

Description

Use `buildmer` to fit big generalized additive models using `gamm` from package `mgcv`

Usage

```
buildgamm(
  formula,
  data = NULL,
  family = gaussian(),
  buildmerControl = buildmerControl(),
```

```
    ...
  )
```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to gamm; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

The fixed and random effects are to be passed as a single formula in lme4 format. This is internally split up into the appropriate fixed and random parts. Only a single grouping factor is allowed. The random-effect covariance matrix is always unstructured. If you want to use pdMat covariance structures, you must (a) *not* specify any lme4 random-effects term in the formula, and (b) specify your own custom random argument as part of the ... argument. Note that buildgamm will merely pass this through; no term reordering or stepwise elimination is done on a user-provided random argument.

See Also

[buildmer-package](#)

Examples

```
library(buildmer)
model <- buildgamm(f1 ~ s(timepoint,by=following) + (following|participant) +
  s(participant,timepoint,by=following,bs='fs'),data=vowels)
```

buildgamm4

Use buildmer to fit generalized additive models using package gamm4

Description

Use buildmer to fit generalized additive models using package gamm4

Usage

```

buildgamm4(
  formula,
  data = NULL,
  family = gaussian(),
  buildmerControl = buildmerControl(),
  ...
)

```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to gamm4; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

The fixed and random effects are to be passed as a single formula in *lme4 format*. This is internally split up into the appropriate fixed and random parts.

See Also

[buildmer-package](#)

Examples

```

library(buildmer)
if (requireNamespace('gamm4')) model <- buildgamm4(f1 ~ s(timepoint,by=following) +
  s(participant,timepoint,by=following,bs='fs'),data=vowels)

```

buildGLMMadaptive	<i>Use buildmer to fit generalized linear mixed models using mixed_model from package GLMMadaptive</i>
-------------------	--

Description

Use buildmer to fit generalized linear mixed models using mixed_model from package GLMMadaptive

Usage

```
buildGLMMadaptive(
  formula,
  data = NULL,
  family,
  buildmerControl = buildmerControl(),
  ...
)
```

Arguments

<code>formula</code>	A formula specifying both fixed and random effects using <code>lme4</code> syntax. (Unlike <code>mixed_model</code> , <code>buildGLMMadaptive</code> does not use a separate random argument!)
<code>data</code>	See the general documentation under buildmer-package
<code>family</code>	See the general documentation under buildmer-package
<code>buildmerControl</code>	Control arguments for <code>buildmer</code> — see the general documentation under buildmerControl
<code>...</code>	Additional options to be passed to <code>mixed_model</code> ; for backward-compatibility reasons, will also accept <code>buildmer</code> control parameters, although those specified in <code>buildmerControl</code> will take precedence

Details

The fixed and random effects are to be passed as a single formula in `lme4 format`. This is internally split up into the appropriate fixed and random parts.

See Also

[buildmer-package](#)

Examples

```
# nonsensical model given these data
if (requireNamespace('GLMMadaptive')) model <- buildGLMMadaptive(stress ~ vowel + (vowel|word),
  family=binomial, data=vowels, nAGQ=1)
```

buildglmmTMB

Use buildmer to perform stepwise elimination on glmmTMB models

Description

Use `buildmer` to perform stepwise elimination on `glmmTMB` models

Usage

```

buildglmmTMB(
  formula,
  data = NULL,
  family = gaussian(),
  buildmerControl = buildmerControl(),
  ...
)

```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to glmmTMB; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

See Also

[buildmer-package](#)

Examples

```

library(buildmer)
if (requireNamespace('glmmTMB')) {
  model <- buildglmmTMB(Reaction ~ Days + (Days|Subject), data=lme4::sleepstudy)
}

```

buildgls	<i>Use buildmer to fit generalized-least-squares models using gls from nlme</i>
----------	---

Description

Use buildmer to fit generalized-least-squares models using gls from nlme

Usage

```

buildgls(formula, data = NULL, buildmerControl = buildmerControl(), ...)

```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to gls; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

A workaround is included to prevent an error when the model matrix is of less than full rank. The summary output of such a model will look a bit strange!

See Also

[buildmer-package](#)

Examples

```
library(buildmer)
library(nlme)
vowels$event <- with(vowels, interaction(participant, word))
model <- buildgls(f1 ~ timepoint*following, correlation=corAR1(form=~1|event), data=vowels)
```

buildlme	<i>Use buildmer to perform stepwise elimination of mixed-effects models fit via lme from nlme</i>
----------	---

Description

Use buildmer to perform stepwise elimination of mixed-effects models fit via lme from nlme

Usage

```
buildlme(formula, data = NULL, buildmerControl = buildmerControl(), ...)
```

Arguments

formula	A formula specifying both fixed and random effects using lme4 syntax. (Unlike lme, buildlme does not use a separate random argument!)
data	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to lme; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

Details

The fixed and random effects are to be passed as a single formula in lme4 format. This is internally split up into the appropriate fixed and random parts. Only a single grouping factor is allowed. The random-effect covariance matrix is always unstructured. If you want to use pdMat covariance structures, you must (a) *not* specify any lme4 random-effects term in the formula, and (b) specify your own custom random argument as part of the `...` argument. Note that `buildlme` will merely pass this through; no term reordering or stepwise elimination is done on a user-provided random argument.

See Also

[buildmer-package](#)

Examples

```
library(buildmer)
model <- buildlme(Reaction ~ Days + (Days|Subject), data=lme4::sleepstudy)
```

buildmer	<i>Use buildmer to fit mixed-effects models using lmer/glmer from lme4</i>
----------	--

Description

Use `buildmer` to fit mixed-effects models using `lmer/glmer` from `lme4`

Usage

```
buildmer(
  formula,
  data = NULL,
  family = gaussian(),
  buildmerControl = buildmerControl(),
  ...
)
```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
buildmerControl	Control arguments for <code>buildmer</code> — see the general documentation under buildmerControl
...	Additional options to be passed to <code>lmer</code> , <code>glmer</code> , or <code>gamm4</code> . (They will also be passed to <code>(g)lm</code> in so far as they're applicable, so you can use arguments like <code>subset=...</code> and expect things to work. The single exception is the <code>control</code> argument, which is assumed to be meant only for <code>lme4</code> and not for <code>(g)lm</code> , and will

not be passed on to (g)lm). For backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence.

Examples

```
library(buildmer)
model <- buildmer(Reaction ~ Days + (Days|Subject),lme4::sleepstudy)

# Tests from github issue #2, that also show the use of the 'direction' and 'crit' parameters:
bm.test <- buildmer(cbind(incidence,size - incidence) ~ period + (1 | herd),
family=binomial,data=lme4::cbpp)
bm.test <- buildmer(cbind(incidence,size - incidence) ~ period + (1 | herd),
family=binomial,data=lme4::cbpp,buildmerControl=buildmerControl(direction='forward'))
bm.test <- buildmer(cbind(incidence,size - incidence) ~ period + (1 | herd),
family=binomial,data=lme4::cbpp,buildmerControl=buildmerControl(crit='AIC'))
bm.test <- buildmer(cbind(incidence,size - incidence) ~ period + (1 | herd),
family=binomial,data=lme4::cbpp,
buildmerControl=buildmerControl(direction='forward',crit='AIC'))
```

buildmer-class

The buildmer class

Description

This is a simple convenience class that allows ‘anova()’ and ‘summary()’ calls to fall through to the underlying model object, while retaining buildmer’s iteration history. If you need to use the final model for other things, such as prediction, access it through the ‘model’ slot of the buildmer class object.

Slots

model The final model containing only the terms that survived elimination
p Parameters used during the fitting process
anova The model’s ANOVA, if the model was built with ‘anova=TRUE’
summary The model’s summary, if the model was built with ‘summary=TRUE’

See Also

[buildmer()]

Examples

```
# Manually create a bare-bones buildmer object:
model <- lm(Sepal.Length ~ Petal.Length,iris)
p <- list(in.buildmer=FALSE)
library(buildmer)
bm <- mkBuildmer(model=model,p=p,anova=NULL,summary=NULL)
summary(bm)
```

buildmerControl *Set control options for buildmer*

Description

buildmerControl() provides all the knobs and levers that can be manipulated during the buildmer fitting and summary()/anova() process. Some of these are part of buildmer's core functionality—for instance, crit allows to specify different elimination criteria, a core buildmer feature—whereas some are only meant for internal usage, e.g. ~I_KNOW_WHAT_I_AM_DOING is only used to turn off the PQL safeguards in buildbam()/buildgam(), which you really should only do if you have a very good reason to believe that the PQL check is being triggered erroneously for your problem.

Usage

```
buildmerControl(
  formula = quote(stop("No formula specified")),
  data = NULL,
  family = gaussian(),
  direction = c("order", "backward"),
  cl = NULL,
  crit = "LRT",
  elim = "LRT",
  fit = function(...) stop("No fitting function specified"),
  include = NULL,
  quiet = FALSE,
  calc.anova = FALSE,
  calc.summary = TRUE,
  ddf = "Wald",
  quickstart = 0,
  dep = NULL,
  can.use.reml = TRUE,
  force.reml = FALSE,
  singular.ok = FALSE,
  grad.tol = formals(buildmer::converged)$grad.tol,
  hess.tol = formals(buildmer::converged)$hess.tol,
  I_KNOW_WHAT_I_AM_DOING = FALSE,
  ...
)
```

Arguments

formula	The model formula for the maximal model you would like to fit. Alternatively, a buildmer term list as obtained from tabulate.formula . In the latter formulation, you also need to specify a dep='...' argument specifying the dependent variable to go along with the term list. See tabulate.formula for an example of where this is useful.
data	The data to fit the model(s) to.

family	The error distribution to use.
direction	Character string or vector indicating the direction for stepwise elimination; possible options are 'order' (order terms by their contribution to the model), 'backward' (backward elimination), 'forward' (forward elimination, implies order). The default is the combination <code>c('order', 'backward')</code> , to first make sure that the model converges and to then perform backward elimination; other such combinations are perfectly allowed.
cl	Specifies a cluster to use for parallelizing the evaluation of terms. This can be an object as returned by function <code>makeCluster</code> from package <code>parallel</code> , or a whole number to let <code>buildmer</code> create, manage, and destroy a cluster for you with the specified number of parallel processes. Note: the various <code>buildmer</code> functions will export a copy of the package namespace to any user-provided cluster; these objects will be cleaned up afterwards, but any pre-existing objects having the same names will be lost. Use <code>'ls(getNamespace('buildmer'),all.names=TRUE)'</code> to obtain a list of object names you should avoid (or rather, be willing to lose).
crit	Character string or vector determining the criterion used to test terms for their contribution to the model fit in the ordering step. Possible options are 'LRT' (likelihood-ratio test based on chi-square mixtures per Stram & Lee 1994 for random effects; this is the default), 'LL' (use the raw -2 log likelihood), 'AIC' (Akaike Information Criterion), 'BIC' (Bayesian Information Criterion), and 'deviance' (explained deviance – note that this is not a formal test).
elim	Character string or vector determining the criterion used to test terms for elimination in the elimination step. Possible options are 'LRT' (likelihood-ratio test based on chi-square mixtures per Stram & Lee 1994 for random effects; this is the default), 'LL' (use the raw -2 log likelihood), 'AIC' (Akaike Information Criterion), 'BIC' (Bayesian Information Criterion), and 'deviance' (explained deviance – note that this is not a formal test).
fit	Internal parameter — do not modify.
include	A one-sided formula or character vector of terms that will be kept in the model at all times. These do not need to be specified separately in the <code>formula</code> argument. Useful for e.g. passing correlation structures in <code>glmmTMB</code> models.
quiet	A logical indicating whether to suppress progress messages.
calc.anova	Logical indicating whether to also calculate the ANOVA table for the final model after term elimination.
calc.summary	Logical indicating whether to also calculate the summary table for the final model after term elimination.
ddf	The method used for calculating p -values for <code>lme4</code> models and <code>calc.anova=TRUE</code> or <code>calc.summary=TRUE</code> . Options are 'Wald' (default), 'Satterthwaite' (if package <code>lmerTest</code> is available), 'Kenward-Roger' (if packages <code>lmerTest</code> and <code>pbkrtest</code> are available), and 'lme4' (no p -values).
quickstart	For <code>gam</code> models only: a numeric with values from 0 to 5. If set to 1, will use <code>bam</code> to obtain starting values for <code>gam</code> 's outer iteration, potentially resulting in a much faster fit for each model. If set to 2, will disregard ML/REML and always use <code>bam</code> 's <code>fREML</code> for the quickstart fit. 3 also sets <code>discrete=TRUE</code> . Values between 3 and 4 fit the quickstart model to a subset of that value (e.g.\

	quickstart=3.1 fits the quickstart model to 10% of the data, which is also the default if quickstart=3. Values between 4 and 5 do the same, but also set a very sloppy convergence tolerance of 0.2.
dep	A character string specifying the name of the dependent variable. Only used if formula is a buildmer terms list.
can.use.reml	Internal option specifying whether the fitting engine should distinguish between fixed-effects and random-effects model comparisons. Do not set this option yourself — this is automatically modified appropriately if you pass a REML option, see Details.
force.reml	Internal option specifying whether, if not differentiating between fixed-effects and random-effects model comparisons, these comparisons should be based on ML or on REML (if possible). Do not set this option yourself — this is automatically modified appropriately if you pass a REML option, see Details.
singular.ok	Logical indicating whether singular fits are acceptable. Only for lme4 models.
grad.tol	Tolerance for declaring gradient convergence. For buildbam, this is multiplied by 100.
hess.tol	Tolerance for declaring Hessian convergence. For buildbam, this is multiplied by 100.
I_KNOW_WHAT_I_AM_DOING	An internal option that you should not modify unless you know what you are doing.
...	Other arguments intended for the fitting function.

Details

With the default options, all buildmer functions will do two things:

1. Determine the order of the effects in your model, based on their importance as measured by the likelihood-ratio test statistic. This identifies the ‘maximal model’, which is the model containing either all effects specified by the user, or subset of those effects that still allow the model to converge, ordered such that the most information-rich effects have made it in.
2. Perform backward stepwise elimination based on the significance of the change in log-likelihood.

The final model is returned in the model slot of the returned buildmer object. All functions in the buildmer package are aware of the distinction between (f)REML and ML, and know to divide chi-square p -values by 2 when comparing models differing only in random effects (see Pinheiro & Bates 2000). The steps executed above can be changed using the `direction` argument, allowing for arbitrary chains of, for instance, forward-backward-forward stepwise elimination (although using more than one elimination method on the same data is not recommended). The criterion for determining the importance of terms in the ordering stage and the elimination of terms in the elimination stage can also be changed, using the `crit` argument.

There are two hidden arguments that buildmer can recognize. These are not part of the formal parameters of the various build* functions, but are recognized by all of them to benefit certain specialist applications:

1. `dep`: It is possible to pass the maximal model formula as a buildmer terms object as obtained via `tabulate.formula`. This allows more control over, for instance, which model terms

should always be evaluated together. If the formula argument is recognized to be such an object (i.e. a data frame), then buildmer will use the string specified in the dep argument as the dependent variable.

2. REML: In some situations, the user may want to force REML on or off, rather than using buildmer's autodetection. If REML=TRUE (or more precisely, if isTRUE(REML) evaluates to true), then buildmer will always use REML. This results in invalid results if formal model-comparison criteria are used with models differing in fixed effects (and the user is not guarded against this), but is useful with the 'deviance-explained' criterion, where it is actually the default (you can disable this and use the 'normal' REML/ML-differentiating behavior by passing REML=NA).

These arguments are not passed on to the fitting function via the ... mechanism.

buildmertree	<i>Use buildmer to perform stepwise elimination for lmer() and glmer() models from package glmer</i>
--------------	--

Description

Use buildmer to perform stepwise elimination for lmer() and glmer() models from package glmer

Usage

```
buildmertree(
  formula,
  data = NULL,
  family = gaussian(),
  buildmerControl = buildmerControl(crit = "AIC"),
  ...
)
```

Arguments

formula	Either a glmer formula, looking like <code>dep ~ left middle right</code> where the middle part is an lme4-style random-effects specification, or an ordinary formula (or buildmer term list thereof) specifying only the dependent variable and the fixed and random effects for the regression part. In the latter case, the additional argument partitioning must be specified as a one-sided formula containing the partitioning part of the model.
data	See the general documentation under buildmer-package
family	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl

... Additional options to be passed to `lmer` or `glmer`. (They will also be passed to `(g)lm` in so far as they're applicable. The single exception is the `control` argument, which is assumed to be meant only for `(g)lm` and not for `(g)lmer`, and will *not* be passed on to `(g)lm`). For backward-compatibility reasons, will also accept `buildmer` control parameters, although those specified in `buildmerControl` will take precedence.

Details

Note that the likelihood-ratio test is not available for `glmer` models, as it cannot be assured that the models being compared are nested. The default is thus to use AIC. In the generalized case or when testing many partitioning variables, it is recommended to pass `joint=FALSE`, as this results in a dramatic speed gain and reduces the odds of the final `glmer` model failing to converge or converging singularly.

See Also

[buildmer-package](#)

Examples

```
if (requireNamespace('glmer')) {
  model <- buildmertree(Reaction ~ 1 | (Days|Subject) | Days,
    buildmerControl=buildmerControl(crit='LL',direction='order'),
    data=lme4::sleepstudy)

  model <- buildmertree(Reaction ~ 1 | (Days|Subject) | Days,
    buildmerControl=buildmerControl(crit='LL',direction='order'),
    data=lme4::sleepstudy,family=Gamma(link=identity),joint=FALSE)
}
```

buildmultinom	<i>Use buildmer to perform stepwise elimination for multinom models from package nnet</i>
---------------	---

Description

Use `buildmer` to perform stepwise elimination for `multinom` models from package `nnet`

Usage

```
buildmultinom(formula, data = NULL, buildmerControl = buildmerControl(), ...)
```

Arguments

formula	See the general documentation under buildmer-package
data	See the general documentation under buildmer-package
buildmerControl	Control arguments for buildmer — see the general documentation under buildmerControl
...	Additional options to be passed to multinom; for backward-compatibility reasons, will also accept buildmer control parameters, although those specified in buildmerControl will take precedence

See Also

[buildmer-package](#)

Examples

```
if (requireNamespace('nnet') && require('MASS')) {
  options(contrasts = c("contr.treatment", "contr.poly"))
  example(birthwt)
  bwt.mu <- buildmultinom(low ~ age*lw*race*smoke,bwt)
}
```

conv	<i>Test a model for convergence – alias for converged(). This is deprecated!</i>
------	--

Description

Test a model for convergence – alias for converged(). This is deprecated!

Usage

```
conv(...)
```

Arguments

... Arguments to be passed to converged()

Value

Logical indicating whether the model converged.

Examples

```
library(buildmer)
library(lme4)
good1 <- lm(Reaction ~ Days, sleepstudy)
good2 <- lmer(Reaction ~ Days + (Days|Subject), sleepstudy)
bad <- lmer(Reaction ~ Days + (Days|Subject), sleepstudy, control=lmerControl(
  optimizer='bobyqa', optCtrl=list(maxfun=1)))
sapply(list(good1, good2, bad), conv)
```

converged

*Test a model for convergence***Description**

Test a model for convergence

Usage

```
converged(model, singular.ok = FALSE, grad.tol = 0.04, hess.tol = 0.002)
```

Arguments

model	The model object to test.
singular.ok	A logical indicating whether singular fits are accepted as ‘converged’ or not. Relevant only for lme4 models.
grad.tol	The tolerance to use for checking the gradient. This is currently only used by mgcv, glmmTMB, and clm(m) models.
hess.tol	The tolerance to use for checking the Hessian for negative eigenvalues. This is currently only used by mgcv, glmmTMB, and clm(m) models.

Value

Logical indicating whether the model converged.

Examples

```
library(buildmer)
library(lme4)
good1 <- lm(Reaction ~ Days, sleepstudy)
good2 <- lmer(Reaction ~ Days + (Days|Subject), sleepstudy)
bad <- lmer(Reaction ~ Days + (Days|Subject), sleepstudy, control=lmerControl(
  optimizer='bobyqa', optCtrl=list(maxfun=1)))
sapply(list(good1, good2, bad), converged)
```

diag, formula-method	<i>Diagonalize the random-effect covariance structure, possibly assisting convergence</i>
----------------------	---

Description

Diagonalize the random-effect covariance structure, possibly assisting convergence

Usage

```
## S4 method for signature 'formula'
diag(x)
```

Arguments

x A model formula.

Value

The formula with all random-effect correlations forced to zero, per Pinheiro & Bates (2000)

Examples

```
# 1. Create explicit columns for factor variables
library(buildmer)
vowels <- cbind(vowels,model.matrix(~vowel,vowels))
# 2. Create formula with diagonal covariance structure
form <- diag(f1 ~ (vowel1+vowel2+vowel3+vowel4)*timepoint*following +
  ((vowel1+vowel2+vowel3+vowel4)*timepoint*following | participant) +
  (timepoint | word))
# 3. Convert formula to buildmer terms list, grouping terms starting with 'vowel'
terms <- tabulate.formula(form,group='vowel[^:]')
# 4. Directly pass the terms object to buildmer(), using the hidden 'dep' argument to specify
# the dependent variable
m <- buildmer(terms,data=vowels,dep='f1')
```

migrant	<i>A very small dataset from a pilot study on sound change.</i>
---------	---

Description

A very small dataset from a pilot study on sound change.

Usage

```
data(migrant)
```


Format

A standard data frame.

re2mgcv

Convert lme4 random-effect terms to mgcv 're' smooths

Description

Convert lme4 random-effect terms to mgcv 're' smooths

Usage

```
re2mgcv(formula, data)
```

Arguments

formula	The lme4 formula.
data	The data.

Examples

```
library(buildmer)
re <- re2mgcv(temp ~ angle + (1|replicate) + (1|recipe),lme4::cake)
model <- buildgam(re$formula,re$data,family=mgcv::scat)
# note: the below does NOT work, as the dependent variable is looked up in the data by name!

re <- re2mgcv(log(Reaction) ~ Days + (Days|Subject),lme4::sleepstudy)
```

remove.terms

Remove terms from an lme4 formula

Description

Remove terms from an lme4 formula

Usage

```
remove.terms(formula, remove)
```

Arguments

formula	The lme4 formula.
remove	A vector of terms to remove. To remove terms nested inside random-effect groups, use '(term group)' syntax. Note that marginality is respected, i.e. no effects will be removed if they participate in a higher-order interaction, and no fixed effects will be removed if a random slope is included over that fixed effect.

Examples

```
library(buildmer)
remove.terms(Reaction ~ Days + (Days|Subject),'(Days|Subject)')
# illustration of the marginality checking mechanism:
remove.terms(Reaction ~ Days + (Days|Subject),'(1|Subject)') #refuses to remove the term
remove.terms(Reaction ~ Days + (Days|Subject),c('(Days|Subject)','(1|Subject)')) #also
#refuses to remove the term, because marginality is checked before removal!
step1 <- remove.terms(Reaction ~ Days + (Days|Subject),'(Days|Subject)')
step2 <- remove.terms(step1,'(1|Subject)') #works
```

tabulate.formula	<i>Parse a formula into a buildmer terms list</i>
------------------	---

Description

Parse a formula into a buildmer terms list

Usage

```
tabulate.formula(formula, group = NULL)
```

Arguments

formula	A formula.
group	A character vector of regular expressions. Terms matching the same regular expression are assigned the same block, and will be evaluated together in buildmer functions.

Value

A buildmer terms list, which is just a normal data frame.

See Also

buildmer-package

Examples

```
form <- diag(f1 ~ (vowel1+vowel2+vowel3+vowel4)*timepoint*following +
  ((vowel1+vowel2+vowel3+vowel4)*timepoint*following|participant) + (timepoint|word))
tabulate.formula(form)
tabulate.formula(form,group='vowel[1-4]')
```

`vowels`*Vowel data from a pilot study.*

Description

Vowel data from a pilot study.

Usage

```
data(vowels)
```

Format

A standard data frame.

Index

* datasets

migrant, [24](#)

vowels, [27](#)

add.terms, [3](#)

build.formula, [3](#)

buildbam, [4](#)

buildclmm, [5](#)

buildcustom, [6](#)

buildgam, [2](#), [8](#)

buildgamm, [9](#)

buildgamm4, [10](#)

buildGLMMadaptive, [11](#)

buildglmmTMB, [12](#)

buildgls, [13](#)

buildlme, [14](#)

buildmer, [2](#), [15](#)

buildmer-class, [16](#)

buildmer-package, [2](#)

buildmerControl, [4](#), [5](#), [7](#), [8](#), [10–15](#), [17](#), [20](#), [22](#)

buildmertree, [2](#), [20](#)

buildmultinom, [21](#)

conv, [22](#)

converged, [23](#)

diag, formula-method, [24](#)

migrant, [24](#)

mkBuildmer (buildmer-class), [16](#)

re2mgcv, [5](#), [9](#), [25](#)

remove.terms, [25](#)

tabulate.formula, [17](#), [19](#), [26](#)

vowels, [27](#)