

Package ‘cpk’

October 12, 2022

Version 1.3-1

Date 2013-12-25

Title Clinical Pharmacokinetics

Description The package cpk provides simplified clinical pharmacokinetic functions for dose regimen design and modification at the point-of-care. Currently, the following functions are available: (1) ttc.fn for target therapeutic concentration, (2) dr.fn for dose rate, (3) di.fn for dosing interval, (4) dm.fn for maintenance dose, (5) bc.ttc.fn for back calculation, (6) ar.fn for accumulation ratio, (7) dpo.fn for orally administered dose, (8) cmax.fn for peak concentration, (9) css.fn for steady-state concentration, (10) cmin.fn for trough,(11) ct.fn for concentration-time predictions, (12) dlcmx.fn for calculating loading dose based on drug's maximum concentration, (13) dlar.fn for calculating loading dose based on drug's accumulation ratio, and (14) R0.fn for calculating drug infusion rate. Reference: Linares O, Linares A. Computational opioid prescribing: A novel application of clinical pharmacokinetics. J Pain Palliat Care Pharmacother 2011;25:125-135.

Depends R (>= 2.10.0)

License GPL-2

Disclaimer The authors take no responsibility for the outcome of therapy in any patient in which the techniques described in this package have been utilized.

Repository CRAN

Date/Publication 2013-12-26 08:12:11

Author Oscar A. Linares [aut, cre],
David T. Daly [aut]

Maintainer Oscar A. Linares <OALinaresMD@gmail.com>

NeedsCompilation no

R topics documented:

cpk-package	2
ar.fn	4
bc.ttc.fn	5
cmax.fn	6

cmin.fn	7
css.fn	7
ct.fn	8
di.fn	9
dlar.fn	10
dlcmax.fn	10
dm.fn	11
dpo.fn	12
dr.fn	12
R0.fn	13
ttc.fn	14

Index	15
--------------	-----------

cpk-package	<i>Clinical Pharmacokinetics.</i>
-------------	-----------------------------------

Description

This package was written to teach concepts and techniques to clinicians and pharmacists for individualizing drug therapy. While the package may be used by clinicians for actual dosage regimen analysis, design, and modification, caution should be exercised when applying the techniques described in R package cpk.

Details

Package: cpk
 Type: Package
 Version: 1.3
 Date: 2013-07-25
 License: GPL-2

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
 Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

Holford, N and Sheiner, LB. Understanding the dose-effect relationship: clinical applications of pharmacokinetic-pharmacodynamic models. *Clin Pharmacokinet* 1981;6:429-453.

Greenblatt D, Koch-Weser J. Clinical pharmacokinetics (First of two parts). *New Engl J Med* 1975;293:702-705.

- Greenblatt D, Koch-Weser J. Clinical pharmacokinetics (Second of two parts). *New Engl J Med* 1975;293:964-970
- Perlin E, Taylor BK, Peck CC. Clinical pharmacokinetics: a simplified approach, part 1. *J Natl Med Assoc* 1985;77:475.
- Perlin E, Taylor R, Peck CC. Clinical pharmacokinetics: a simplified approach, part 2. *J Natl Med Assoc* 1986;78:835.
- Shafer SL, Varvel JR. Pharmacokinetics, pharmacodynamics, and rational opioid selection. *Anesthesiology* 1991;74:53-63.
- Mehvar R. Pharmacokinetic-based design and modification of dosage regimens. *Am J Pharmaceut Educ* 1998;62:189-195.
- Brocks DR, Mehvar R. Rate and extent of drug accumulation after multiple dosing revisited. *Clin Pharmacokinet* 2010;49:421-438.
- Jannetto PJ, Bratanow NC. Utilization of pharmacogenomics and therapeutic drug monitoring for opioid pain management. *Pharmacogenomics* 2009;10(7):1157-67.
- Jannetto PJ, Bratanow NC. Pain management in the 21st century: Utilization of pharmacogenomics and therapeutic drug monitoring. *Expet Opin Drug Metabol Toxicol* 2012;7(6):745-52.
- Linares OA. Pharmacokinetics-based opioid prescribing: Case report. *The Pain Practitioner* 2010;20:19-21.
- Linares O, Linares A. Computational opioid prescribing: A novel application of clinical pharmacokinetics. *J Pain Palliat Care Pharmacother* 2011;25:125-135.
- Linares OA, Daly D, Stefanovski D, Boston RC. A new model for using quantitative urine testing as a diagnostic tool for oxycodone treatment and compliance. *J Pain Palliat Care Pharmacother* 2013;27:(in press).

Examples

```

wtkg = 181;      # kg

# Drug Disposition Parameters
thalf = 4;      # h
ke    = 0.3180; # h^-1
vd    = 4.5;    # L/kg
cl    = 1.43;   # L/h/kg
f     = 1.00;   # dpo range: 15-64% (avg 38%), IV f = 1.

#### Set TTC
ttc = 25;

#### Calculate dose rate (mg/h)
dr  <- dr.fn (ttc, cl, wtkg, f)

#### Set dosing interval based on thalf
di = 4;  # h

#### Calculate dose (if f = 1, dose IV)
dpo <- dpo.fn (dr, di)

```

```

dpo/1000 # convert to mg

#### Calculate loading dose based on cmax
cmax <- 18.93; vd <- 35;
dlcmax <- dlcmax.fn(cmax, vd)

#### Calculate loading dose based on ar
dm <- 276; ar <- 2.4;
dlar <- dlar.fn(dm, ar)

#-----
# ANALYSIS
#-----
bc.ttc <- bc.ttc.fn (dr, f, cl, wtkg)

#### predict avg steady-state concentration
# accumulation ratio
ar <- ar.fn (ke, di)

css <- css.fn (f, dpo, di, cl, ar, wtkg)
css # mg/L

# predict fluctuation about steady-state (ug/L)
cmax <- cmax.fn (f, dpo, vd, ar, wtkg)
cmin <- cmin.fn (cmax, ke, di)

ct <- ct.fn(cmax, ke, time=0)
ct <- ct.fn(cmax, ke, time=4)

# infusion rate
css <- 14.43; cl <- 3.2;
R0 <- R0.fn(css, cl)

```

ar.fn

Accumulation ratio function

Description

Calculates drug's accumulation ratio

Usage

```
ar.fn(ke, di)
```

Arguments

ke	Drug's total elimination rate constant ke (h ⁻¹).
di	Dosing interval (h).

Value

Returns the calculated accumulation ratio

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

Examples

```
ke <- 0.2350; di <- 4;  
ar <- ar.fn(ke, di)
```

bc.ttc.fn

Back-calculation function

Description

Performs a back-calculation to get the target therapeutic concentration (TTC) based on the administered dose.

Usage

```
bc.ttc.fn(dr, f, cl, wtkg)
```

Arguments

dr	dr is
f	bioavailability
cl	clearance rate
wtkg	weight in kg average man in US (NHANES III)

Value

Returns the back-calculated TTC (ug/L).

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
ttc <- 20; dr <- 2.26; cl <- 0.57; f <- 0.74; wtkg <- 86;  
dr <- dr.fn(ttc,cl,wtkg,f)
```

cmax.fn

cmax function

Description

Calculates cmax (peak) drug concentration in ng/mL, which is the same as ug/mL.

Usage

```
cmax.fn(f, dpo, vd, ar, wtkg)
```

Arguments

f	is bioavailability.
dpo	is oral dose administered in ug.
vd	is apparent volume of distribution in L.
ar	is accumulation ratio.
wtkg	is patient weight in kg.

Value

Returns cmax ug/L.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
f = 0.74; dpo <- 3440; vd = 2.8; ar = 2.4; wtkg=86;  
cmax <- cmax.fn(f, dpo, vd, ar, wtkg)
```

cmin.fn	<i>cmin function</i>
---------	----------------------

Description

Calculates cmin (trough) drug concentration in ng/mL, which is the same as ug/mL.

Usage

```
cmin.fn(cmax, ke, di)
```

Arguments

cmax	is the maximum concentration of drug (peak level).
ke	Drug's total elimination rate constant.
di	is the dosing interval in h.

Value

Returns cmin ug/L.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
cmax <- 25.37; ke <- 0.1333; di <- 4;  
cmin <- cmin.fn(cmax, ke, di)
```

css.fn	<i>css function</i>
--------	---------------------

Description

Calculates css (steady-state) drug concentration in ng/mL, which is the same as ug/mL.

Usage

```
css.fn(f, dpo, di, cl, ar, wtkg)
```

Arguments

f	is bioavailability.
dpo	is oral dose administered in ug.
di	is the dosing interval in h.
cl	is the total clearance rate in L/kg/h.
ar	is stepwise accumulation ratio.
wtkg	is patient weight in kg.

Value

Returns css in mg/L and ug/L

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
f <- 0.74; dpo <- 3440; di <- 4; cl <- 0.37; ar <-1.4; wtkg <- 86;  
css <-css.fn(f, dpo, di, cl, ar, wtkg)
```

ct.fn

ct function

Description

Predicts drug concentration at specified time (default time=0 h) [ng/mL].

Usage

```
ct.fn(cmax, ke, time=0)
```

Arguments

cmax	is the maximum concentration (cmax).
ke	is the first-order elimination rate constant (ke).
time	is the time on the clearance curve for which a drug concentration is desired.

Value

Returns the concentration at specified time.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
cmax <- 15; ke <- 0.1333; time <- 4;  
ct <- ct.fn(cmax, ke, time=0)
```

di.fn

di function

Description

Calculates a drug's dosing interval.

Usage

```
di.fn(msc, mec, ke)
```

Arguments

msc	Drug's maximum safe concentration or Cmax (peak) concentration.
mec	Drug's minimum effective concentration or Cmin (trough) concentration.
ke	Drug's total elimination rate constant.

Value

Returns the dosing interval (h).

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
msc <- 50; mec <- 20; ke <- 0.2078;  
di <- di.fn(msc, mec, ke)
```

dlar.fn *Loading dose function*

Description

Calculates a drug's loading dose based on its accumulation ratio

Usage

```
dlar.fn(dm, ar)
```

Arguments

dm	Drug's maintenance dose.
ar	Drug's accumulation ratio.

Value

Returns the calculated loading dose

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

Examples

```
dm <- 276; ar <- 2.4;  
dlar <- dlar.fn(dm, ar)
```

dlcmax.fn *Loading dose function*

Description

Calculates a drug's loading dose based on its cmax

Usage

```
dlcmax.fn(cmax, vd)
```

Arguments

cmax	Drug's maximum concentration (cmax).
vd	Drug's apparent volume of distribution (vd).

Value

Returns the calculated loading dose

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

Examples

```
cmax <- 18.93; vd <- 35;  
dlcmax <- dlcmax.fn(cmax, vd)
```

dm.fn

dm function

Description

Calculates drug's maintenance dose.

Usage

```
dm.fn(dr, di)
```

Arguments

dr is the dose rate.
di is the dosing interval, which can be either computed or assigned (e.g., di <- 4)

Value

Returns the maintenance dose.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
dr <- 1.42; di <- 4;  
dm <- dm.fn(dr, di)
```

dpo.fn

dpo function

Description

Calculates the oral dose of drug to give.

Usage

```
dpo.fn(dr, di)
```

Arguments

dr is the dose rate in mg/h.
di is the dosing interval in h.

Value

Returns oral dose administered in ug.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
dr <- 0.86; di <- 4;  
dpo <- dpo.fn(dr, di)
```

dr.fn

dr function

Description

Calculates dose rate (mg/h).

Usage

```
dr.fn(ttc, cl, wtkg, f)
```

Arguments

ttc	target therapeutic concentration.
cl	clearance rate.
wtkg	patient's weight in kilograms.
f	bioavailability.

Value

Returns the dose rate.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
ttc <- 32.74; cl <- 0.59; wtkg <- 86; f <- 0.74;  
dr <- dr.fn(ttc, cl, wtkg, f)
```

R0.fn

R0 function

Description

Predicts drug infusion rate [ug/h].

Usage

```
R0.fn(css, cl)
```

Arguments

css	is the steady-state concentration.
cl	is the clearance rate.

Value

Returns the infusion rate.

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
css <- 14.43; cl <- 3.2;  
R0 <- R0.fn(css, cl)
```

ttc.fn

ttc function

Description

Calculates a drug's target therapeutic concentration (ttc) based on its msc or cmax and mec or cmin in ng/mL, which is the same as ug/mL.

Usage

```
ttc.fn(msc, mec)
```

Arguments

msc	maximum safe concentration or cmax
mec	minimum effective concentration of cmin

Value

Returns target therapeutic concentration (ttc).

Author(s)

Oscar A. Linares MD and David T. Daly JD/MBA.
Maintainer: Oscar A. Linares MD <OALinaresMD@gmail.com>

References

See **cpk-package** help.

Examples

```
msc = 50; mec = 20;  
ttc <- ttc.fn(msc, mec)
```

Index

* **cpk package**

cpk-package, 2

ar. fn, 4

bc.ttc. fn, 5

cmax. fn, 6

cmin. fn, 7

cpk (cpk-package), 2

cpk-package, 2

css. fn, 7

ct. fn, 8

di. fn, 9

dlar. fn, 10

dlcmax. fn, 10

dm. fn, 11

dpo. fn, 12

dr. fn, 12

R0. fn, 13

ttc. fn, 14