Package 'gamstransfer'

September 9, 2026

Type Package

Title A Data Interface Between 'GAMS' and R

Version 3.0.9

Date 2026-09-09

Maintainer Atharv Bhosekar <abhosekar@gams.com>

Description Read, analyze, modify, and write 'GAMS' (General Algebraic Modeling System) data. The main focus of 'gamstransfer' is the highly efficient transfer of data with 'GAMS' <https://www.gams.com/>, while keeping these operations as simple as possible for the user. The transfer of data usually takes place via an intermediate GDX (GAMS Data Exchange) file. Additionally, 'gamstransfer' provides utility functions to get an overview of 'GAMS' data and to check its validity.

License MIT + file LICENSE

Imports Rcpp (>= 1.0.6), R6 (>= 2.5.1), R.utils (>= 2.11.0), collections(>= 0.3.6)

LinkingTo Rcpp

Suggests testthat (>= 3.0.0)

URL https://github.com/GAMS-dev/transfer-r/tree/main/gamstransfer

BugReports https://github.com/GAMS-dev/transfer-r/issues

Config/testthat/edition 3

RoxygenNote 7.3.2

SystemRequirements C++17

Encoding UTF-8

Collate 'Alias.R' 'BaseAlias.R' 'Container.R' 'DomainViolation.R' 'SpecialValues.R' 'Equation.R' 'Parameter.R' 'RcppExports.R' 'Set.R' 'Super.R' 'Symbol.R' 'UniverseAlias.R' 'Variable.R' 'gamstransfer-package.R' 'symbolTypes.R' 'utility.R'

NeedsCompilation yes

Author Atharv Bhosekar [aut, cre], GAMS Development Corp. [cph, fnd], GAMS Software GmbH [cph, fnd]

Repository CRAN

Date/Publication 2026-09-09 12:00:07 UTC

Contents

.Symbol 2
Alias 2
Container 3
DomainViolation 4
Equation 4
Parameter 5
readGDX 5
Set 6
SpecialValues 6
UniverseAlias 7
Variable 7
writeGDX 7

Index **9**

`.Symbol` *Symbol Abstract Class*

Description

An abstract symbol class from which the classes Set, Parameter, Variable, and Equation are inherited. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

`Alias` *Alias Class*

Description

A class for Alias objects. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
# create a container
m <- Container$new()
# add a set
i <- Set$new(m, "i")
# add an alias to the set "i"
ii <- Alias$new(m, "ii", i)
```

Container *Container Class*

Description

The main object class within GAMS Transfer is called Container. The Container is the vessel that allows symbols to be linked together (through their domain definitions), it enables implicit set definitions, it enables structural manipulations of the data (matrix generation), and it allows the user to perform different read/write operations. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Create a new container simply by initializing an object.

Usage

```
Container(loadFrom = NULL)
```

Arguments

loadFrom	optional argument to point to the GDX file being read into the Container

Fields

`data` is a named list containing all symbol data

Examples

```
m <- Container$new()
i <- m$addSet("i")
j <- m$addSet("j")
all_symbols <- m$listSymbols()
set_description <- m$describeSets()
# create a container and read the file trnsport.gdx
m = Container$new(system.file("extdata", "trnsport.gdx", package = "gamstransfer"))
# access symbol named "x" from the container
x = m["x"]
# list all symbols
all_symbols = m$listSymbols()
# list all sets
all_sets = m$listSets()
# check if the container contains symbol named "i"
has_i = m$hasSymbols("i")
# get a summary of the description of all sets in the Container
set_description = m$describeSets()
```

DomainViolation *DomainViolation Class*

Description

Contains information about the domain violation for a symbol. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Fields

`symbol` symbol name

`dimension` dimension in which domain violation is present

`domain` domain name

`violations` vector of violations

Examples

```
m <- Container$new()
i <- Set$new(m, "i", records = paste0("i", 1:5))
p <- Parameter$new(m, "p", i, records = data.frame(i = c("i1", "i3", "i6"), value = c(1, 5, 7)))
dv <- p$getDomainViolations()[[1]]
sym_dv <- dv$symbol
dim_dv <- dv$dimension
domain_dv <- dv$domain
violation_dv <- dv$violations
```

Equation *Equation Class*

Description

A class for Equation objects. This class inherits from an abstract symbol class.The documentation for methods common to all symbols can be accessed via help(.Symbol). Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
# create a container
m <- Container$new()
# add a Variable
e <- Equation$new(m, "v", type = "eq")
# access records
e_recs <- e$records
```

Parameter *Parameter Class*

Description

A class for Parameter objects. This class inherits from an abstract Symbol class.The documentation for methods common to all symbols can be accessed via help(.Symbol). Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
# create a container
m <- Container$new()
# add a Parameter
p <- Parameter$new(m, "p")
# access records
p_recs <- p$records
```

readGDX *readGDX*

Description

read a GDX file to a list without creating symbol or container objects

Usage

```
readGDX(loadFrom, symbols = NULL, records = TRUE)
```

Arguments

loadFrom	name of the GDX file being read (string)
symbols	optional argument - vector of strings containing the symbol names to be read
records	optional logical argument - TRUE (default) to read the symbol records, FALSE to only read the meta data. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
read_list <- readGDX(system.file("extdata", "trnsport.gdx", package = "gamstransfer"))
```

Set *Set Class*

Description

A class for Set objects. This class inherits from an abstract Symbol class. The documentation for methods common to all symbols can be accessed via help(.Symbol). Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
# create a container
m <- Container$new()
# add a set
i <- Set$new(m, "i")
# access records
i_recs <- i$records
```

SpecialValues *SpecialValues list object*

Description

This list contains GAMS special values and helper functions to check if a given value is a GAMS special value. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Usage

```
SpecialValues
```

Format

An object of class `list` of length 10.

Examples

```
# check the value of GAMS special value NA
NA_val <- SpecialValues[["NA"]]
# check the value of GAMS special value EPS
EPS_val <- SpecialValues[["EPS"]]
# check if a value is GAMS special value `NA`
isNA_check <- SpecialValues$isNA(0)
```

UniverseAlias *UniverseAlias Class*

Description

A class for Alias objects that are aliased to the Universe set. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

#' @examples # create a container m = Container$new() # add a UniverseAlias u = UniverseAlias$new(m, "u")

Variable *Variable Class*

Description

A class for Variable objects. This class inherits from an abstract Symbol class. Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
# create a container
m <- Container$new()
# add a Variable
v <- Variable$new(m, "v")
# access records
v_recs <- v$records
```

writeGDX *writeGDX*

Description

write a GDX file from a list containing symbol data and metadata

Usage

```
writeGDX(
  writeList,
  writeTo,
  symbols = NULL,
  compress = FALSE,
  uelPriority = NULL,
  mode = NULL
)
```

Arguments

writeList	list containing symbol data and metadata
writeTo	name of the output GDX file
symbols	optional argument - vector of strings containing the symbol names to be read
compress	optional logical argument. TRUE to produce a compressed GDX file
uelPriority	Specify the priority UELs
mode	optional string argument to specify the write mode ("string", "mapped"). Please visit https://transfer-r.readthedocs.io/en/latest/ for detailed documentation of this package.

Examples

```
writeGDX(list(), tempfile(fileext = ".gdx"))
```

Index

∗ **datasets**
    SpecialValues, 6
.Symbol, 2

Alias, 2

Container, 3

DomainViolation, 4

Equation, 4

Parameter, 5

readGDX, 5

Set, 6
SpecialValues, 6

UniverseAlias, 7

Variable, 7

writeGDX, 7