

Package ‘graphlayouts’

May 1, 2023

Title Additional Layout Algorithms for Network Visualizations

Version 1.0.0

Description

Several new layout algorithms to visualize networks are provided which are not part of ‘igraph’. Most are based on the concept of stress majorization by Gansner et al. (2004) <[doi:10.1007/978-3-540-31843-9_25](https://doi.org/10.1007/978-3-540-31843-9_25)>.

Some more specific algorithms allow the user to emphasize hidden group structures in networks or focus on specific nodes.

URL <http://graphlayouts.schochastics.net/>,
<https://github.com/schochastics/graphlayouts>

BugReports <https://github.com/schochastics/graphlayouts/issues>

Depends R (>= 3.2.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports igraph, Rcpp

Suggests oaqc, testthat, ggraph, ggplot2, knitr, rmarkdown, uwot

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.2.3

VignetteBuilder knitr

NeedsCompilation yes

Author David Schoch [aut, cre] (<<https://orcid.org/0000-0003-2952-4812>>)

Maintainer David Schoch <david@schochastics.net>

Repository CRAN

Date/Publication 2023-05-01 08:00:02 UTC

R topics documented:

annotate_circle	2
draw_circle	3
graph_manipulate	4
layout_backbone	5
layout_centrality	6
layout_centrality_group	8
layout_constrained_stress	9
layout_constrained_stress3D	10
layout_dynamic	11
layout_focus	13
layout_focus_group	14
layout_manipulate	15
layout_multilevel	16
layout_pmds	18
layout_sparse_stress	19
layout_spectral	20
layout_stress	21
layout_stress3D	23
layout_umap	24
multlvl_ex	25

Index	26
--------------	-----------

annotate_circle	<i>annotate concentric circles</i>
-----------------	------------------------------------

Description

annotate concentric circles

Usage

```
annotate_circle(cent, col = "#00BFFF", format = "", pos = "top", text_size = 3)
```

Arguments

cent	centrality scores used for layout
col	color of text
format	either empty string or 'scientific'
pos	position of text ('top' or 'bottom')
text_size	font size for annotations

Details

this function is best used with [layout_with_centrality](#) together with [draw_circle](#).

Value

annotated concentric circles around origin

Examples

```
library(igraph)
library(ggraph)

g <- sample_gnp(10,0.4)
## Not run:
ggraph(g,layout = "centrality",centrality = closeness(g))+
  draw_circle(use = "cent")+
  annotate_circle(closeness(g),pos = "bottom",format = "scientific")+
  geom_edge_link()+
  geom_node_point(shape=21,fill="grey25",size=5)+
  theme_graph()+
  coord_fixed()

## End(Not run)
```

draw_circle

Draw concentric circles

Description

Draw concentric circles

Usage

```
draw_circle(col = "#00BFFF", use = "focus", max.circle)
```

Arguments

col	color of circles
use	one of 'focus' or 'cent'
max.circle	if use = 'focus' specifies the number of circles to draw

Details

this function is best used with a concentric layout such as [layout_with_focus](#) and [layout_with_centrality](#).

Value

concentric circles around origin

Examples

```
library(igraph)
library(ggraph)
g <- sample_gnp(10,0.4)

## Not run:
ggraph(g,layout = "centrality",centrality = degree(g))+
  draw_circle(use = "cent")+
  geom_edge_link()+
  geom_node_point(shape = 21,fill = "grey25",size = 5)+
  theme_graph()+
  coord_fixed()

## End(Not run)
```

graph_manipulate *Manipulate graph*

Description

functions to manipulate a graph

Usage

```
reorder_edges(g, attr, desc = TRUE)
```

Arguments

g	igraph object
attr	edge attribute name used to sort edges
desc	logical. sort in descending (default) or ascending order

Details

reorder_edges() allows to reorder edges according to an attribute so that edges are drawn in the given order.

Value

manipulated graph

Author(s)

David Schoch

Examples

```
library(igraph)
library(ggraph)

g <- sample_gnp(10,0.5)
E(g)$attr <- 1:ecount(g)
gn <- reorder_edges(g,"attr")
```

layout_backbone	<i>backbone graph layout</i>
-----------------	------------------------------

Description

emphasizes a hidden group structure if it exists in the graph. Calculates a layout for a sparsified network only including the most embedded edges. Deleted edges are added back after the layout is calculated.

Usage

```
layout_as_backbone(g, keep = 0.2, backbone = TRUE)

layout_igraph_backbone(g, keep = 0.2, backbone = TRUE, circular)
```

Arguments

<code>g</code>	igraph object
<code>keep</code>	fraction of edges to keep during backbone calculation
<code>backbone</code>	logical. Return edge ids of the backbone (Default: TRUE)
<code>circular</code>	not used

Details

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'. 'ggraph' natively supports the layout.

Value

list of xy coordinates and vector of edge ids included in the backbone

References

Nocaj, A., Ortmann, M., & Brandes, U. (2015). Untangling the hairballs of multi-centered, small-world online social media networks. *Journal of Graph Algorithms and Applications: JGAA*, 19(2), 595-618.

Examples

```
library(igraph)

g <- sample_islands(9,20,0.4,9)
g <- simplify(g)
V(g)$grp <- as.character(rep(1:9,each=20))
bb <- layout_as_backbone(g,keep=0.4)

# add backbone links as edge attribute
E(g)$col <- FALSE
E(g)$col[bb$backbone] <- TRUE
```

layout_centrality *radial centrality layout*

Description

arranges nodes in concentric circles according to a centrality index.

Usage

```
layout_with_centrality(
  g,
  cent,
  scale = TRUE,
  iter = 500,
  tol = 1e-04,
  tseq = seq(0, 1, 0.2)
)
```

```
layout_igraph_centrality(
  g,
  cent,
  scale = TRUE,
  iter = 500,
  tol = 1e-04,
  tseq = seq(0, 1, 0.2),
  circular
)
```

Arguments

g	igraph object
cent	centrality scores
scale	logical. should centrality scores be scaled to [0, 100]? (Default: TRUE)

iter	number of iterations during stress optimization
tol	stopping criterion for stress optimization
tseq	numeric vector. increasing sequence of coefficients to combine regular stress and constraint stress. See details.
circular	not used

Details

The function optimizes a convex combination of regular stress and a constrained stress function which forces nodes to be arranged on concentric circles. The vector `tseq` is the sequence of parameters used for the convex combination. In iteration i of the algorithm $tseq[i]$ is used to combine regular and constraint stress as $(1 - tseq[i]) * stress_{regular} + tseq[i] * stress_{constraint}$. The sequence must be increasing, start at zero and end at one. The default setting should be a good choice for most graphs.

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'. 'ggraph' natively supports the layout.

Value

matrix of xy coordinates

References

Brandes, U., & Pich, C. (2011). More flexible radial layout. *Journal of Graph Algorithms and Applications*, 15(1), 157-173.

See Also

[layout_centrality_group](#)

Examples

```
library(igraph)
library(ggraph)

g <- sample_gnp(10,0.4)
## Not run:
ggraph(g,layout="centrality",centrality = closeness(g))+
  draw_circle(use = "cent")+
  geom_edge_link0()+
  geom_node_point(shape = 21,fill = "grey25",size = 5)+
  theme_graph()+
  coord_fixed()

## End(Not run)
```

layout_centrality_group

radial centrality group layout

Description

arranges nodes in concentric circles according to a centrality index and keeping groups within a angle range

Usage

```
layout_with_centrality_group(g, cent, group, shrink = 10, ...)
```

```
layout_igraph_centrality_group(g, cent, group, shrink = 10, circular, ...)
```

Arguments

g	igraph object
cent	centrality scores
group	vector indicating grouping of nodes
shrink	shrink the reserved angle range for a group to increase the gaps between groups
...	additional arguments to layout_with_centrality The layout_igraph_* function should not be used directly. It is only used as an argument for plotting with 'igraph'. 'ggraph' natively supports the layout.
circular	not used

Value

matrix of xy coordinates

See Also

[layout_centrality](#)

Examples

```
library(igraph)
```

layout_constrained_stress
constrained stress layout

Description

force-directed graph layout based on stress majorization with variable constrained

Usage

```
layout_with_constrained_stress(  
  g,  
  coord,  
  fixdim = "x",  
  weights = NA,  
  iter = 500,  
  tol = 1e-04,  
  mds = TRUE,  
  bbox = 30  
)  
  
layout_igraph_constrained_stress(  
  g,  
  coord,  
  fixdim = "x",  
  weights = NA,  
  iter = 500,  
  tol = 1e-04,  
  mds = TRUE,  
  bbox = 30,  
  circular  
)
```

Arguments

<code>g</code>	igraph object
<code>coord</code>	numeric vector. fixed coordinates for dimension specified in <code>fixdim</code> .
<code>fixdim</code>	string. which dimension should be fixed. Either "x" or "y".
<code>weights</code>	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
<code>iter</code>	number of iterations during stress optimization
<code>tol</code>	stopping criterion for stress optimization
<code>mds</code>	should an MDS layout be used as initial layout (default: TRUE)

bbox	constrain dimension of output. Only relevant to determine the placement of disconnected graphs
circular	not used

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together ($weights=1/E(g)\$weight$).

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'. 'ggraph' natively supports the layout.

Value

matrix of xy coordinates

References

Gansner, E. R., Koren, Y., & North, S. (2004). Graph drawing by stress majorization. *In International Symposium on Graph Drawing* (pp. 239-250). Springer, Berlin, Heidelberg.

See Also

[layout_constrained_stress3D](#)

layout_constrained_stress3D
constrained stress layout in 3D

Description

force-directed graph layout based on stress majorization with variable constrained in 3D

Usage

```
layout_with_constrained_stress3D(
  g,
  coord,
  fixdim = "x",
  weights = NA,
  iter = 500,
  tol = 1e-04,
  mds = TRUE,
  bbox = 30
)
```

Arguments

<code>g</code>	igraph object
<code>coord</code>	numeric vector. fixed coordinates for dimension specified in <code>fixdim</code> .
<code>fixdim</code>	string. which dimension should be fixed. Either "x", "y" or "z".
<code>weights</code>	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
<code>iter</code>	number of iterations during stress optimization
<code>tol</code>	stopping criterion for stress optimization
<code>mds</code>	should an MDS layout be used as initial layout (default: TRUE)
<code>bbox</code>	constrain dimension of output. Only relevant to determine the placement of disconnected graphs

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together ($weights=1/E(g)$weight$).

This function does not come with direct support for `igraph` or `ggraph`.

Value

matrix of xyz coordinates

References

Gansner, E. R., Koren, Y., & North, S. (2004). Graph drawing by stress majorization. *In International Symposium on Graph Drawing* (pp. 239-250). Springer, Berlin, Heidelberg.

See Also

[layout_constrained_stress](#)

layout_dynamic	<i>dynamic graph layout</i>
----------------	-----------------------------

Description

Create layouts for longitudinal networks.

Usage

```
layout_as_dynamic(gList, weights = NA, alpha = 0.5, iter = 500, tol = 1e-04)
```

Arguments

<code>gList</code>	list of igraph objects. Each network must contain the same set of nodes.
<code>weights</code>	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
<code>alpha</code>	weighting of reference layout. See details.
<code>iter</code>	number of iterations during stress optimization
<code>tol</code>	stopping criterion for stress optimization

Details

The reference layout is calculated based on the union of all graphs. The parameter alpha controls the influence of the reference layout. For alpha=1, only the reference layout is used and all graphs have the same layout. For alpha=0, the stress layout of each individual graph is used. Values in-between interpolate between the two layouts.

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together (`weights=1/E(g)$weight`).

Value

list of coordinates for each graph

References

Brandes, U. and Indlekofer, N. and Mader, M. (2012). Visualization methods for longitudinal social networks and stochastic actor-oriented modeling. *Social Networks* 34 (3) 291-308

Examples

```
library(igraph)
g1 <- sample_gnp(20,0.2)
g2 <- sample_gnp(20,0.2)
g3 <- sample_gnp(20,0.2)

xy <- layout_as_dynamic(list(g1,g2,g3))

# layout for first network
xy[[1]]
```

layout_focus	<i>radial focus layout</i>
--------------	----------------------------

Description

arrange nodes in concentric circles around a focal node according to their distance from the focus.

Usage

```
layout_with_focus(g, v, weights = NA, iter = 500, tol = 1e-04)
```

```
layout_igraph_focus(g, v, weights = NA, iter = 500, tol = 1e-04, circular)
```

Arguments

<code>g</code>	igraph object
<code>v</code>	id of focal node to be placed in the center
<code>weights</code>	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
<code>iter</code>	number of iterations during stress optimization
<code>tol</code>	stopping criterion for stress optimization
<code>circular</code>	not used

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together ($\text{weights}=1/E(g)\$weight$).

Value

a list containing xy coordinates and the distances to the focal node

References

Brandes, U., & Pich, C. (2011). More flexible radial layout. *Journal of Graph Algorithms and Applications*, 15(1), 157-173.

See Also

[layout_focus_group](#) The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'. 'ggraph' natively supports the layout.

Examples

```
library(igraph)
g <- sample_gnp(10,0.4)
coords <- layout_with_focus(g,v = 1)
coords
```

layout_focus_group *radial focus group layout*

Description

arrange nodes in concentric circles around a focal node according to their distance from the focus and keep predefined groups in the same angle range.

Usage

```
layout_with_focus_group(
  g,
  v,
  group,
  shrink = 10,
  weights = NA,
  iter = 500,
  tol = 1e-04
)

layout_igraph_focus_group(
  g,
  v,
  group,
  shrink = 10,
  weights = NA,
  iter = 500,
  tol = 1e-04,
  circular
)
```

Arguments

g	igraph object
v	id of focal node to be placed in the center
group	vector indicating grouping of nodes
shrink	shrink the reserved angle range for a group to increase the gaps between groups
weights	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.

iter	number of iterations during stress optimization
tol	stopping criterion for stress optimization
circular	not used

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together ($\text{weights}=1/E(g)\$weight$).

Value

matrix of xy coordinates

See Also

[layout_focus](#) The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'.

Examples

```
library(igraph)
g <- sample_islands(4,5,0.8,2)
grp <- as.character(rep(1:4,each = 5))
layout_with_focus_group(g,v = 1, group = grp, shrink = 10)
```

layout_manipulate *manipulate layout*

Description

functions to manipulate an existing layout

Usage

```
layout_rotate(xy, angle)

layout_mirror(xy, axis = "vertical")
```

Arguments

xy	graph layout
angle	angle for rotation
axis	mirror horizontal or vertical

Details

These functions are mostly useful for deterministic layouts such as [layout_with_stress](#)

Value

manipulated matrix of xy coordinates

Author(s)

David Schoch

Examples

```
library(igraph)
g <- sample_gnp(50,0.3)

xy <- layout_with_stress(g)

#rotate 90 degrees
xy <- layout_rotate(xy,90)

# flip horizontally
xy <- layout_mirror(xy,"horizontal")
```

layout_multilevel *multilevel layout*

Description

Layout algorithm to visualize multilevel networks

Usage

```
layout_as_multilevel(
  g,
  type = "all",
  FUN1,
  FUN2,
  params1 = NULL,
  params2 = NULL,
  ignore_iso = TRUE,
  project2D = TRUE,
  alpha = 35,
  beta = 45
)

layout_igraph_multilevel(
  g,
  type = "all",
  FUN1,
  FUN2,
```



```

    params1 = NULL,
    params2 = NULL,
    ignore_iso = TRUE,
    alpha = 35,
    beta = 45,
    circular
)

```

Arguments

<code>g</code>	igraph object. Must have a vertex attribute "lvl" which is 1 or 2.
<code>type</code>	one of "all", "separate", "fix1" or "fix2". see details
<code>FUN1</code>	if type="separate", the layout function to be used for level 1
<code>FUN2</code>	if type="separate", the layout function to be used for level 2
<code>params1</code>	named list of parameters for FUN1
<code>params2</code>	named list of parameters for FUN2
<code>ignore_iso</code>	treatment of isolates within levels. see details
<code>project2D</code>	logical. Defaults to TRUE (project to 2D).
<code>alpha</code>	angle for isometric projection between 0 and 90
<code>beta</code>	angle for isometric projection between 0 and 90
<code>circular</code>	not used

Details

The algorithm internally computes a 3D layout where each level is in a separate y-plane. The layout is then projected into 2D via an isometric mapping, controlled by the parameters `alpha` and `beta`. It may take some adjusting to `alpha` and `beta` to find a good perspective.

If type="all", the layout is computed at once for the complete network. For type="separate", two user specified layout algorithms (FUN1 and FUN2) are used for the levels. The named lists `param1` and `param2` can be used to set parameters for FUN1 and FUN2. This option helpful for situations where different structural features of the levels should be emphasized.

For type="fix1" and type="fix2" only one of the level layouts is fixed. The other one is calculated by optimizing the inter level ties, such that they are drawn (almost) vertical.

The `ignore_iso` parameter controls the handling of isolates. If TRUE, nodes without inter level edges are ignored during the layout process and added at the end. If FALSE they are left unchanged

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'.

Value

matrix of xy coordinates

Examples

```

library(igraph)
data("multilvl_ex")

# compute a layout for the whole network
xy <- layout_as_multilevel(multilvl_ex, type = "all", alpha = 25, beta = 45)

# compute a layout for each level separately and combine them
xy <- layout_as_multilevel(multilvl_ex, type = "separate",
                          FUN1 = layout_as_backbone,
                          FUN2 = layout_with_stress,
                          alpha = 25, beta = 45)

```

layout_pmds

pivot MDS graph layout

Description

similar to [layout_with_mds](#) but uses only a small set of pivots for MDS. Considerably faster than MDS and thus applicable for larger graphs.

Usage

```
layout_with_pmds(g, pivots, weights = NA, D = NULL, dim = 2)
```

```
layout_igraph_pmds(g, pivots, weights = NA, D = NULL, circular)
```

Arguments

g	igraph object
pivots	number of pivots
weights	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
D	precomputed distances from pivots to all nodes (if available, default: NULL)
dim	dimensionality of layout (defaults to 2)
circular	not used

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together (`weights=1/E(g)$weight`)

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with `'igraph'`. `'ggraph'` natively supports the layout.

Value

matrix of coordinates

Author(s)

David Schoch

References

Brandes, U. and Pich, C. (2006). Eigensolver Methods for Progressive Multidimensional Scaling of Large Data. In *International Symposium on Graph Drawing* (pp. 42-53). Springer

Examples

```
## Not run:  
library(igraph)  
library(ggraph)  
  
g <- sample_gnp(1000,0.01)  
  
xy <- layout_with_pmds(g,pivots = 100)  
  
## End(Not run)
```

layout_sparse_stress *sparse stress graph layout*

Description

stress majorization for larger graphs based on a set of pivot nodes.

Usage

```
layout_with_sparse_stress(g, pivots, weights = NA, iter = 500)  
  
layout_igraph_sparse_stress(g, pivots, weights = NA, iter = 500, circular)
```

Arguments

g	igraph object
pivots	number of pivots
weights	ignored
iter	number of iterations during stress optimization
circular	not used

Details

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with `'igraph'`. `'ggraph'` natively supports the layout.

Value

matrix of xy coordinates

Author(s)

David Schoch

References

Ortmann, M. and Klimenta, M. and Brandes, U. (2016). A Sparse Stress Model. <https://arxiv.org/pdf/1608.08909.pdf>

Examples

```
## Not run:
library(igraph)
library(ggraph)

g <- sample_gnp(1000,0.005)

ggraph(g,layout = "sparse_stress",pivots = 100)+
  geom_edge_link0(edge_colour = "grey66")+
  geom_node_point(shape = 21,fill = "grey25",size = 5)+
  theme_graph()

## End(Not run)
```

layout_spectral	<i>spectral graph layouts</i>
-----------------	-------------------------------

Description

Using a set of eigenvectors of matrices associated with a graph as coordinates

Usage

```
layout_with_eigen(g, type = "laplacian", ev = "smallest")

layout_igraph_eigen(g, type = "laplacian", ev = "smallest", circular)
```

Arguments

<code>g</code>	igraph object
<code>type</code>	matrix to be used for spectral decomposition. either <code>'adjacency'</code> or <code>'laplacian'</code>
<code>ev</code>	eigenvectors to be used. Either <code>'smallest'</code> or <code>'largest'</code> .
<code>circular</code>	not used

Details

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with `'igraph'`. `'ggraph'` natively supports the layout.

Value

matrix of xy coordinates

Author(s)

David Schoch

Examples

```
library(igraph)

g <- sample_gnp(50,0.2)

xy <- layout_with_eigen(g,type = "adjacency",ev = "largest")
xy <- layout_with_eigen(g,type = "adjacency",ev = "smallest")
xy <- layout_with_eigen(g,type = "laplacian",ev = "largest")
xy <- layout_with_eigen(g,type = "laplacian",ev = "smallest")
```

layout_stress	<i>stress majorization layout</i>
---------------	-----------------------------------

Description

force-directed graph layout based on stress majorization.

Usage

```
layout_with_stress(  
  g,  
  weights = NA,  
  iter = 500,  
  tol = 1e-04,  
  mds = TRUE,  
  bbox = 30  
)  
  
layout_igraph_stress(  
  g,  
  weights = NA,  
  iter = 500,
```

```

    tol = 1e-04,
    mds = TRUE,
    bbox = 30,
    circular
  )

```

Arguments

<code>g</code>	igraph object
<code>weights</code>	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
<code>iter</code>	number of iterations during stress optimization
<code>tol</code>	stopping criterion for stress optimization
<code>mds</code>	should an MDS layout be used as initial layout (default: TRUE)
<code>bbox</code>	width of layout. Only relevant to determine the placement of disconnected graphs
<code>circular</code>	not used

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together ($weights=1/E(g)$weight$).

The `layout_igraph_*` function should not be used directly. It is only used as an argument for plotting with 'igraph'. 'ggraph' natively supports the layout.

Value

matrix of xy coordinates

References

Gansner, E. R., Koren, Y., & North, S. (2004). Graph drawing by stress majorization. *In International Symposium on Graph Drawing* (pp. 239-250). Springer, Berlin, Heidelberg.

See Also

[layout_stress3D](#)

Examples

```

library(igraph)
library(ggraph)
set.seed(665)

g <- sample_pa(100,1,1,directed = FALSE)

```

```

# calculate layout manually
xy <- layout_with_stress(g)

# use it with ggraph
## Not run:
ggraph(g,layout = "stress")+
  geom_edge_link0(edge_width = 0.2,colour = "grey")+
  geom_node_point(col = "black",size = 0.3)+
  theme_graph()

## End(Not run)

```

layout_stress3D	<i>stress majorization layout in 3D</i>
-----------------	---

Description

force-directed graph layout based on stress majorization in 3D.

Usage

```

layout_with_stress3D(
  g,
  weights = NA,
  iter = 500,
  tol = 1e-04,
  mds = TRUE,
  bbox = 30
)

```

Arguments

g	igraph object
weights	possibly a numeric vector with edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). By default, weights are ignored. See details for more.
iter	number of iterations during stress optimization
tol	stopping criterion for stress optimization
mds	should an MDS layout be used as initial layout (default: TRUE)
bbox	width of layout. Only relevant to determine the placement of disconnected graphs

Details

Be careful when using weights. In most cases, the inverse of the edge weights should be used to ensure that the endpoints of an edges with higher weights are closer together ($weights=1/E(g)$weight$).

Value

matrix of xyz coordinates

References

Gansner, E. R., Koren, Y., & North, S. (2004). Graph drawing by stress majorization. *In International Symposium on Graph Drawing* (pp. 239-250). Springer, Berlin, Heidelberg.

See Also

[layout_stress](#)

layout_umap	<i>UMAP graph layouts</i>
-------------	---------------------------

Description

Using the UMAP dimensionality reduction algorithm as a graph layout

Usage

```
layout_with_umap(g, pivots = NULL, ...)
```

```
layout_igraph_umap(g, circular, ...)
```

Arguments

g	igraph object
pivots	if not NULL, number of pivot nodes to use for distance calculation (for large graphs).
...	additional parameters for umap. See the ?uwot : : umap for help.
circular	not used

Details

The layout_igraph_* function should not be used directly. It is only used as an argument for plotting with 'igraph'. UMAP can be tuned by many different parameters. Refer to the documentation at <https://github.com/jlmelville/uwot> for help

Value

matrix of xy coordinates

Author(s)

David Schoch

References

McInnes, Leland, John Healy, and James Melville. "Umap: Uniform manifold approximation and projection for dimension reduction." arXiv preprint arXiv:1802.03426 (2018).

Examples

```
library(igraph)

g <- sample_islands(10,20,0.6,10)
xy <- layout_with_umap(g,min_dist = 0.5)
```

multlvl_ex

Multilevel example Network

Description

Multilevel network, where both levels have different structural features

Usage

```
multlvl_ex
```

Format

igraph object

Index

- * **datasets**
 - multilvl_ex, 25
- annotate_circle, 2
- draw_circle, 2, 3
- graph_manipulate, 4
- layout_as_backbone (layout_backbone), 5
- layout_as_dynamic (layout_dynamic), 11
- layout_as_multilevel (layout_multilevel), 16
- layout_backbone, 5
- layout_centrality, 6, 8
- layout_centrality_group, 7, 8
- layout_constrained_stress, 9, 11
- layout_constrained_stress3D, 10, 10
- layout_dynamic, 11
- layout_focus, 13, 15
- layout_focus_group, 13, 14
- layout_igraph_backbone (layout_backbone), 5
- layout_igraph_centrality (layout_centrality), 6
- layout_igraph_centrality_group (layout_centrality_group), 8
- layout_igraph_constrained_stress (layout_constrained_stress), 9
- layout_igraph_eigen (layout_spectral), 20
- layout_igraph_focus (layout_focus), 13
- layout_igraph_focus_group (layout_focus_group), 14
- layout_igraph_multilevel (layout_multilevel), 16
- layout_igraph_pmds (layout_pmds), 18
- layout_igraph_sparse_stress (layout_sparse_stress), 19
- layout_igraph_stress (layout_stress), 21
- layout_igraph_umap (layout_umap), 24
- layout_manipulate, 15
- layout_mirror (layout_manipulate), 15
- layout_multilevel, 16
- layout_pmds, 18
- layout_rotate (layout_manipulate), 15
- layout_sparse_stress, 19
- layout_spectral, 20
- layout_stress, 21, 24
- layout_stress3D, 22, 23
- layout_umap, 24
- layout_with_centrality, 2, 3
- layout_with_centrality (layout_centrality), 6
- layout_with_centrality_group (layout_centrality_group), 8
- layout_with_constrained_stress (layout_constrained_stress), 9
- layout_with_constrained_stress3D (layout_constrained_stress3D), 10
- layout_with_eigen (layout_spectral), 20
- layout_with_focus, 3
- layout_with_focus (layout_focus), 13
- layout_with_focus_group (layout_focus_group), 14
- layout_with_mds, 18
- layout_with_pmds (layout_pmds), 18
- layout_with_sparse_stress (layout_sparse_stress), 19
- layout_with_stress, 15
- layout_with_stress (layout_stress), 21
- layout_with_stress3D (layout_stress3D), 23
- layout_with_umap (layout_umap), 24
- multilvl_ex, 25
- reorder_edges (graph_manipulate), 4