

Package ‘hystReet’

June 14, 2020

Type Package

Title Get Pedestrian Frequency Data from the 'Hystreet' Project

Date 2020-06-14

Version 0.0.2

Maintainer Johannes Friedrich <Johannes.Friedrich@posteo.de>

Description An R API wrapper for the 'Hystreet' project <<https://hystreet.com>>. 'Hystreet' provides pedestrian counts in different cities in Germany.

URL <https://github.com/JohannesFriedrich/hystReet>

BugReports <https://github.com/JohannesFriedrich/hystReet/issues>

License GPL-2

Depends R (>= 3.5.0), httr, jsonlite, lubridate

Suggests dplyr, ggplot2, htmltools, knitr, rmarkdown, scales

LazyData true

RoxygenNote 7.1.0

Encoding UTF-8

VignetteBuilder knitr

NeedsCompilation no

Author Johannes Friedrich [aut, cre]

Repository CRAN

Date/Publication 2020-06-14 07:40:03 UTC

R topics documented:

hystReet-package	2
corona_data_all	2
data_73_74	3
get_hystreet_locations	3
get_hystreet_station_data	4
get_hystreet_stats	5

locations	6
location_71	6
ratio	6
set_hystreet_token	7

Index	8
--------------	----------

hystReet-package	<i>hystReet</i>
------------------	-----------------

Description

An R API wrapper for the hystreet project. Download and analyse environmental data provided by <https://hystreet.com/>

Details

Package: hystReet
 Type: Package
 Version: 0.0.2
 Date: 2020-06-14
 License: GPL-2

corona_data_all	<i>Downloaded data for the vignette</i>
-----------------	---

Description

Downloaded data for the vignette

Format

data.frame with all available stations in March 2020

Author(s)

Johannes Friedrich

data_73_74	<i>Downloaded data for the vignette</i>
------------	---

Description

Downloaded data for the vignette

Format

data.frame with pedestrians counta from January 2019

Author(s)

Johannes Friedrich

get_hystreet_locations	<i>Get station IDs of the Hystreet project</i>
------------------------	--

Description

Get station IDs of the Hystreet project

Usage

```
get_hystreet_locations(API_token = NULL)
```

Arguments

API_token **character (optional)**: API key to get access to Hystreet API

Value

[data.frame](#) with parsed data from hystreet API

Function version

0.0.2

Author(s)

Johannes Friedrich

Examples

```
## Not run:  
get_hystreet_locations()  
  
## End(Not run)
```

get_hystreet_station_data

Get data from a specific location from the Hystreet Project via Hystreet API

Description

Get data from a specific location from the Hystreet Project via Hystreet API

Usage

```
get_hystreet_station_data(hystreetId = NULL, query = NULL, API_token = NULL)
```

Arguments

hystreetId	integer (required) : ID of the requested station. See get_hystreet_locations() for an overview of available IDs.
query	list (optional) : A list with queries. Up to date the following queries are supported: <ul style="list-style-type: none">• from: datetime of earliest measurement (default: today 00:00:00): e.g. "2018-10-01 12:00:00" or "2018-10-01"• to : datetime of latest measurement (default: today 23:59:59): e.g. "2018-01-12 12:00:00" or "2018-12-01"• resolution: Resolution for the measurement grouping (default: hour): "day", "hour", "month", "week"
API_token	character (optional) : API key to get access to Hystreet API

Value

[data.frame](#) with parsed data from hystreet API

Function version

0.0.2

Author(s)

Johannes Friedrich

Examples

```
## Not run:  
## request data of the current day of station with hystreetId 71  
get_hystreet_station_data(71)  
  
## request data of December 2018 with resolution "day"  
get_hystreet_station_data(
```

```
hystreetId = 71,  
query = list(from = "2018-12-01", to = "2018-12-31", resolution = "day"))  
  
## End(Not run)
```

get_hystreet_stats *Get statistics from the Hystreet Project via Hystreet API*

Description

Get statistics from the Hystreet Project via Hystreet API

Usage

```
get_hystreet_stats(verbose = FALSE, API_token = NULL)
```

Arguments

verbose **logical (optional)**: Show more verbose output?
API_token **character (optional)**: API key to get access to Hystreet API

Value

[data.frame](#) with parsed data from hystreet API

Function version

0.0.2

Author(s)

Johannes Friedrich

Examples

```
## Not run:  
get_hystreet_stats(TRUE)  
  
## End(Not run)
```

locations	<i>Downloaded data for the vignette</i>
-----------	---

Description

Downloaded data for the vignette

Format

data.frame with all available locations (03/27/2020)

Author(s)

Johannes Friedrich

location_71	<i>Downloaded data for the vignette</i>
-------------	---

Description

Downloaded data for the vignette

Format

list with results from location 71 in december 2018

Author(s)

Johannes Friedrich

ratio	<i>Downloaded data for the vignette</i>
-------	---

Description

Downloaded data for the vignette

Format

data.frame with pedestrians count/day

Author(s)

Johannes Friedrich

set_hystreet_token *Set your API token for the Hystreet API*

Description

Set your API token for the Hystreet API

Usage

```
set_hystreet_token(API_token = NULL)
```

Arguments

API_token **character (required)**: API key to get access to Hystreet API

Value

Set environment variable

Function version

0.0.1

Author(s)

Johannes Friedrich

Index

*Topic **package**

hystReet-package, 2

character, 3–5, 7

corona_data_all, 2

data.frame, 3–5

data_73_74, 3

get_hystreet_locations, 3

get_hystreet_locations(), 4

get_hystreet_station_data, 4

get_hystreet_stats, 5

hystReet-package, 2

integer, 4

list, 4

location_71, 6

locations, 6

logical, 5

ratio, 6

set_hystreet_token, 7