Package 'mlr3tuningspaces'

July 25, 2026

Title Search Spaces for 'mlr3'

Version 0.7.0

Description Collection of search spaces for hyperparameter optimization in the 'mlr3' ecosystem. It features ready-to-use search spaces for many popular machine learning algorithms. The search spaces are from scientific articles and work for a wide range of data sets.

License LGPL-3

URL https://mlr3tuningspaces.mlr-org.com, https://github.com/mlr-org/mlr3tuningspaces

BugReports https://github.com/mlr-org/mlr3tuningspaces/issues

Depends mlr3tuning (>= 0.15.0), R (>= 3.1.0)

Imports cli, checkmate (>= 2.0.0), data.table (>= 1.14.0), mlr3 (>= 0.11.0), mlr3misc (>= 0.11.0), paradox (>= 0.7.1), R6 (>= 2.5.0)

Suggests e1071 (>= 1.7-6), bbotk, glmnet (>= 4.1-2), mlr3learners (>= 0.4.5), mlr3pipelines, ranger (>= 0.12.1), rpart (>= 4.1-15), testthat (>= 3.0.0), xgboost (>= 1.4.1.1), torch (>= 0.15.0), mlr3torch (>= 0.3)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

Collate 'mlr_tuning_spaces.R' 'TuningSpace.R' 'bibentries.R' 'sugar.R' 'tuning_spaces_default.R' 'tuning_spaces_rbv1.R' 'tuning_spaces_rbv2.R' 'tuning_spaces_rtdl.R' 'zzz.R'

NeedsCompilation no

Author Marc Becker [cre, aut] (ORCID: <https://orcid.org/0000-0002-8115-0400>), Michel Lang [ctb] (ORCID: <https://orcid.org/0000-0001-9754-0393>)

Maintainer Marc Becker <marcbecker@posteo.de>

Repository CRAN

Date/Publication 2026-07-25 11:50:02 UTC

Contents

mlr3tuningspaces-package 2
lts 3
mlr_tuning_spaces 4
mlr_tuning_spaces_default 5
mlr_tuning_spaces_rbv1 6
mlr_tuning_spaces_rbv2 7
mlr_tuning_spaces_rtdl 9
TuningSpace 10

Index **14**

`mlr3tuningspaces-package`

mlr3tuningspaces: Search Spaces for 'mlr3'

Description

Collection of search spaces for hyperparameter optimization in the 'mlr3' ecosystem. It features ready-to-use search spaces for many popular machine learning algorithms. The search spaces are from scientific articles and work for a wide range of data sets.

Author(s)

Maintainer: Marc Becker <marcbecker@posteo.de> (ORCID)

Other contributors:

- Michel Lang <michellang@gmail.com> (ORCID) [contributor]

See Also

Useful links:

- https://mlr3tuningspaces.mlr-org.com
- https://github.com/mlr-org/mlr3tuningspaces
- Report bugs at https://github.com/mlr-org/mlr3tuningspaces/issues

lts *Syntactic Sugar for Tuning Space Construction*

Description

Function to retrieve TuningSpace objects from mlr_tuning_spaces and further, allows a mlr3::Learner to be directly configured with a search space. This function belongs to mlr3::mlr_sugar family.

Usage

```
lts(x, ...)

## S3 method for class 'missing'
lts(x, ...)

## S3 method for class 'character'
lts(x, ...)

## S3 method for class 'Learner'
lts(x, ...)

ltss(x)
```

Arguments

x	(character() | mlr3::Learner) If character, key passed the dictionary to retrieve the tuning space. If mlr3::Learner, default tuning space is added to the learner.
...	(named list of paradox::TuneToken | NULL) Pass paradox::TuneToken to add or overwrite parameters in the tuning space. Use NULL to remove parameters (see examples).

Value

TuningSpace if x is character(). mlr3::Learner if x is mlr3::Learner. Or a list of objects for the ltss() function.

missing, mlr_tuning_spaces dictionary

a character, TuningSpace

a mlr3::Learner, mlr3::Learner with paradox::TuneToken

a list(), list of TuningSpace or mlr3::Learner

Examples

```
# load tuning space
lts("classif.rpart.default")
```

```
# load tuning space and add parameter
lts("classif.rpart.default", maxdepth = to_tune(1, 15))

# load tuning space and remove parameter
lts("classif.rpart.default", minsplit = NULL)

# load tuning space and overwrite parameter
lts("classif.rpart.default", minsplit = to_tune(32, 128))

# load learner and apply tuning space in one go
lts(lrn("classif.rpart"))

# load learner, overwrite parameter and apply tuning space
lts(lrn("classif.rpart"), minsplit = to_tune(32, 128))

# load multiple tuning spaces
ltss(c("classif.rpart.default", "classif.ranger.default"))
```

`mlr_tuning_spaces` *Dictionary of Tuning Spaces*

Description

A simple mlr3misc::Dictionary storing objects of class TuningSpace. Each tuning space has an associated help page, see `mlr_tuning_spaces_[id]`.

Format

R6::R6Class object inheriting from mlr3misc::Dictionary.

Methods

See mlr3misc::Dictionary.

S3 methods

- `as.data.table(dict, ..., objects = FALSE)`
  mlr3misc::Dictionary -> `data.table::data.table()`
  Returns a `data.table::data.table()` with fields "key", "label", "learner", and "n_values" as columns. If `objects` is set to `TRUE`, the constructed objects are returned in the list column named `object`.

Examples

```
as.data.table(mlr_tuning_spaces)
mlr_tuning_spaces$get("classif.ranger.default")
lts("classif.ranger.default")
```

`mlr_tuning_spaces_default` *Default Tuning Spaces*

Description

Tuning spaces from the Bischl (2023) article.

glmnet tuning space

- s $[1e-04, 10000]$ Logscale
- alpha $[0, 1]$

ranger tuning space

- mtry.ratio $[0, 1]$
- replace [TRUE,FALSE]
- sample.fraction $[0.1, 1]$
- num.trees $[1, 2000]$

rpart tuning space

- minsplit $[2, 128]$ Logscale
- minbucket $[1, 64]$ Logscale
- cp $[1e-04, 0.1]$ Logscale

svm tuning space

- cost $[1e-04, 10000]$ Logscale
- kernel [“polynomial”, “radial”, “sigmoid”, “linear”]
- degree $[2, 5]$
- gamma $[1e-04, 10000]$ Logscale

xgboost tuning space

- eta $[1e-04, 1]$ Logscale
- nrounds $[1, 5000]$
- max_depth $[1, 20]$
- colsample_bytree $[0.1, 1]$
- colsample_bylevel $[0.1, 1]$
- lambda $[0.001, 1000]$ Logscale
- alpha $[0.001, 1000]$ Logscale
- subsample $[0.1, 1]$

Source

Bischl B, Binder M, Lang M, Pielok T, Richter J, Coors S, Thomas J, Ullmann T, Becker M, Boulesteix A, Deng D, Lindauer M (2023). "Hyperparameter Optimization: Foundations, Algorithms, Best Practices and Open Challenges."

`mlr_tuning_spaces_rbv1`

RandomBot Tuning Spaces

Description

Tuning spaces from the Kuehn (2018) article.

glmnet tuning space

- alpha $[0, 1]$
- s $[1e-04, 1000]$ Logscale

ranger tuning space

- num.trees $[1, 2000]$
- replace [TRUE,FALSE]
- sample.fraction $[0.1, 1]$
- mtry.ratio $[0, 1]$
- respect.unordered.factors ["ignore", "order"]
- min.node.size $[1, 100]$

The tuning space of the ranger learner is slightly different from the original paper. The hyperparameter `mtry.power` is replaced by `mtry.ratio` and `min.node.size` is explored in a range from 1 to 100.

rpart tuning space

- cp $[0, 1]$
- maxdepth $[1, 30]$
- minbucket $[1, 60]$
- minsplit $[1, 60]$

svm tuning space

- kernel ["linear", "polynomial", "radial"]
- cost $[1e-04, 1000]$ Logscale
- gamma $[1e-04, 1000]$ Logscale
- degree $[2, 5]$

xgboost tuning space

- nrounds $[1, 5000]$
- eta $[1e-04, 1]$ Logscale
- subsample $[0, 1]$
- booster [“gblinear”, “gbtree”, “dart”]
- max_depth $[1, 15]$
- min_child_weight $[1, 100]$ Logscale
- colsample_bytree $[0, 1]$
- colsample_bylevel $[0, 1]$
- lambda $[1e-04, 1000]$ Logscale
- alpha $[1e-04, 1000]$ Logscale

Source

Kuehn D, Probst P, Thomas J, Bischl B (2018). “Automatic Exploration of Machine Learning Experiments on OpenML.” 1806.10961, https://arxiv.org/abs/1806.10961.

`mlr_tuning_spaces_rbv2`

RandomBot V2 Tuning Spaces

Description

Tuning spaces from the Binder (2020) article.

glmnet tuning space

- alpha $[0, 1]$
- s $[1e-04, 1000]$ Logscale

ranger tuning space

- num.trees $[1, 2000]$
- replace [TRUE,FALSE]
- sample.fraction $[0.1, 1]$
- mtry.ratio $[0, 1]$
- respect.unordered.factors [“ignore”, “order”, “partition”]
- min.node.size $[1, 100]$
- splitrule [“gini”, “extratrees”]
- num.random.splits $[1, 100]$

`mtry.power` is replaced by `mtry.ratio`.

rpart tuning space

- cp $[1e-04, 1]$ Logscale
- maxdepth $[1, 30]$
- minbucket $[1, 100]$
- minsplit $[1, 100]$

svm tuning space

- kernel ["linear", "polynomial", "radial"]
- cost $[1e-04, 1000]$ Logscale
- gamma $[1e-04, 1000]$ Logscale
- tolerance $[1e-04, 2]$ Logscale
- degree $[2, 5]$

xgboost tuning space

- booster ["gblinear", "gbtree", "dart"]
- nrounds $[7, 2981]$ Logscale
- eta $[1e-04, 1]$ Logscale
- gamma $[1e-05, 7]$ Logscale
- lambda $[1e-04, 1000]$ Logscale
- alpha $[1e-04, 1000]$ Logscale
- subsample $[0.1, 1]$
- max_depth $[1, 15]$
- min_child_weight $[1, 100]$ Logscale
- colsample_bytree $[0.01, 1]$
- colsample_bylevel $[0.01, 1]$
- rate_drop $[0, 1]$
- skip_drop $[0, 1]$

Source

Binder M, Pfisterer F, Bischl B (2020). "Collecting Empirical Data About Hyperparameters for Data Driven AutoML." https://www.automl.org/wp-content/uploads/2020/07/AutoML_2020_paper_63.pdf.

`mlr_tuning_spaces_rtdl`

Deep Learning Tuning Spaces from Yandex's RTDL

Description

Tuning spaces for deep neural network architectures from the Gorishniy (2021) article.

These tuning spaces require optimizers that have a `weight_decay` parameter, such as AdamW or any of the other optimizers built into `mlr3torch`.

When the article suggests multiple ranges for a given hyperparameter, these tuning spaces choose the widest range.

The FT-Transformer tuning space disables weight decay for all bias parameters, matching the implementation provided by the authors in the rtdl-revisiting-models package. However, this differs from the experiments described in the article, which states that the

For the FT-Transformer, if training is unstable, consider a combination of standardizing features, using an adaptive optimizer (e.g. Adam), reducing the learning rate, and using a learning rate scheduler.

MLP tuning space

- n_layers $[1, 16]$
- neurons -
- p $[0, 0.5]$
- opt.lr $[1e-05, 0.01]$ Logscale
- opt.weight_decay $[1e-06, 0.001]$ Logscale
- epochs $[1, 100]$
- patience 17

Tabular ResNet tuning space

- n_blocks $[1, 16]$
- d_block $[64, 1024]$
- d_hidden_multiplier $[1, 4]$
- dropout1 $[0, 0.5]$
- dropout2 $[0, 0.5]$
- opt.lr $[1e-05, 0.01]$ Logscale
- opt.weight_decay $[1e-06, 0.001]$ Logscale
- epochs $[1, 100]$
- patience 17

FT-Transformer tuning space

- n_blocks $[1, 6]$
- d_token $[8, 64]$
- attention_n_heads 8
- residual_dropout $[0, 0.2]$
- attention_dropout $[0, 0.5]$
- ffn_dropout $[0, 0.5]$
- ffn_d_hidden_multiplier $[0.666666666666667, 2.66666666666667]$
- opt.lr $[1e-05, 1e-04]$ Logscale
- opt.weight_decay $[1e-06, 0.001]$ Logscale
- opt.param_groups -
- epochs $[1, 100]$
- patience 17

In the FT-Transformer, the validation-related parameters must still be set manually, via e.g. `lts("regr.ft_transformer.rt` `= 0.2, measures_valid = msr("regr.rmse"))`.

Source

Gorishniy Y, Rubachev I, Khrulkov V, Babenko A (2021). "Revisiting Deep Learning for Tabular Data." *arXiv*, **2106.11959**.

`TuningSpace` *Tuning Spaces*

Description

This class defines a tuning space for hyperparameter tuning.

For tuning, it is important to create a search space that defines the range over which hyperparameters should be tuned. `TuningSpace` object consists of search spaces from peer-reviewed articles which work well for a wide range of data sets.

The `$values` field stores a list of paradox::TuneToken which define the search space. These tokens can be assigned to the `$values` slot of a learner's paradox::ParamSet. When the learner is tuned, the tokens are used to create the search space.

S3 Methods

- `as.data.table.TuningSpace(x)`
  Returns a tabular view of the tuning space.
  TuningSpace -> `data.table::data.table()`

  - x (TuningSpace)

Public fields

`id (character(1))`
Identifier of the object.

`values (list())`
List of paradox::TuneToken that describe the tuning space and fixed parameter values.

`tags (character())`
Arbitrary tags to group and filter tuning space e.g. `"classification"` or `"regression"`.

`learner (character(1))`
mlr3::Learner of the tuning space.

`package (character(1))`
Packages which provide the mlr3::Learner, e.g. **mlr3learners** for the learner mlr3learners::LearnerClassifRanger which interfaces the **ranger** package.

`label (character(1))`
Label for this object. Can be used in tables, plot and text output instead of the ID.

`man (character(1))`
String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

Methods

Public methods:

- `TuningSpace$new()`
- `TuningSpace$get_learner()`
- `TuningSpace$format()`
- `TuningSpace$help()`
- `TuningSpace$print()`
- `TuningSpace$clone()`

Method `new()`**:** Creates a new instance of this R6 class.

Usage:

```
TuningSpace$new(
  id,
  values,
  tags,
  learner,
  package = character(),
  label = NA_character_,
  man = NA_character_
)
```

Arguments:

`id (character(1))`
Identifier for the new instance.

`values (list())`
List of paradox::TuneToken that describe the tuning space and fixed parameter values.

`tags (character())`
Tags to group and filter tuning spaces e.g. `"classification"` or `"regression"`.

`learner (character(1))`
mlr3::Learner of the tuning space.

`package (character())`
Packages which provide the mlr3::Learner, e.g. **mlr3learners** for the learner mlr3learners::LearnerClassifRanger which interfaces the **ranger** package.

`label (character(1))`
Label for the new instance. Can be used in tables, plot and text output instead of the ID.

`man (character(1))`
String in the format `[pkg]::[topic]` pointing to a manual page for for the new instance. The referenced help package can be opened via method `$help()`.

Method `get_learner()`**:** Returns a learner with paradox::TuneToken set in parameter set.

Usage:

```
TuningSpace$get_learner(...)
```

Arguments:

`...` (named 'list()')
Passed to `mlr3::lrn()`. Named arguments passed to the constructor, to be set as parameters in the paradox::ParamSet, or to be set as public field. See `mlr3misc::dictionary_sugar_get()` for more details.

Returns: mlr3::Learner

Method `format()`**:** Helper for print outputs.

Usage:

```
TuningSpace$format(...)
```

Arguments:

`...` (ignored).

Method `help()`**:** Opens the corresponding help page referenced by field `$man`.

Usage:

```
TuningSpace$help()
```

Method `print()`**:** Printer.

Usage:

```
TuningSpace$print(...)
```

Arguments:

`...` (ignored).

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
TuningSpace$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3tuning)

# Get default tuning space of rpart learner
tuning_space = lts("classif.rpart.default")

# Set tuning space
learner = lrn("classif.rpart")
learner$param_set$values = tuning_space$values

# Tune learner
instance = tune(
  tnr("random_search"),
  task = tsk("sonar"),
  learner = learner,
  resampling = rsmp ("holdout"),
  measure = msr("classif.ce"),
  term_evals = 10)

instance$result

library(mlr3pipelines)

# Set tuning space in a pipeline
graph_learner = as_learner(po("subsample") %>>%
  lts(lrn("classif.rpart")))
```

Index

∗ **Dictionary**
    mlr_tuning_spaces, 4
∗ **TuningSpace**
    mlr_tuning_spaces, 4
∗ **datasets**
    mlr_tuning_spaces, 4

data.table::data.table(), *4*, *10*

lts, 3
ltss *(*lts*)*, 3

mlr3::Learner, *3*, *11*, *12*
mlr3::mlr_sugar, *3*
mlr3learners::LearnerClassifRanger, *11*, *12*
mlr3misc::Dictionary, *4*
mlr3tuningspaces *(*mlr3tuningspaces-package*)*, 2
mlr3tuningspaces-package, 2
mlr_tuning_spaces, *3*, 4
mlr_tuning_spaces_classif.ft_transformer.rtdl *(*mlr_tuning_spaces_rtdl*)*, 9
mlr_tuning_spaces_classif.glmnet.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_classif.glmnet.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_classif.glmnet.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_classif.mlp.rtdl *(*mlr_tuning_spaces_rtdl*)*, 9
mlr_tuning_spaces_classif.ranger.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_classif.ranger.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_classif.ranger.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_classif.rpart.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_classif.rpart.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_classif.rpart.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_classif.svm.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_classif.svm.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_classif.svm.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_classif.tab_resnet.rtdl *(*mlr_tuning_spaces_rtdl*)*, 9
mlr_tuning_spaces_classif.xgboost.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_classif.xgboost.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_classif.xgboost.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_default, 5
mlr_tuning_spaces_rbv1, 6
mlr_tuning_spaces_rbv2, 7
mlr_tuning_spaces_regr.ft_transformer.rtdl *(*mlr_tuning_spaces_rtdl*)*, 9
mlr_tuning_spaces_regr.glmnet.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_regr.glmnet.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_regr.glmnet.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_regr.mlp.rtdl *(*mlr_tuning_spaces_rtdl*)*, 9
mlr_tuning_spaces_regr.ranger.default *(*mlr_tuning_spaces_default*)*, 5
mlr_tuning_spaces_regr.ranger.rbv1 *(*mlr_tuning_spaces_rbv1*)*, 6
mlr_tuning_spaces_regr.ranger.rbv2 *(*mlr_tuning_spaces_rbv2*)*, 7
mlr_tuning_spaces_regr.rpart.default *(*mlr_tuning_spaces_default*)*, 5

mlr_tuning_spaces_regr.rpart.rbv1
(mlr_tuning_spaces_rbv1), 6
mlr_tuning_spaces_regr.rpart.rbv2
(mlr_tuning_spaces_rbv2), 7
mlr_tuning_spaces_regr.svm.default
(mlr_tuning_spaces_default), 5
mlr_tuning_spaces_regr.svm.rbv1
(mlr_tuning_spaces_rbv1), 6
mlr_tuning_spaces_regr.svm.rbv2
(mlr_tuning_spaces_rbv2), 7
mlr_tuning_spaces_regr.tab_resnet.rtdl
(mlr_tuning_spaces_rtdl), 9
mlr_tuning_spaces_regr.xgboost.default
(mlr_tuning_spaces_default), 5
mlr_tuning_spaces_regr.xgboost.rbv1
(mlr_tuning_spaces_rbv1), 6
mlr_tuning_spaces_regr.xgboost.rbv2
(mlr_tuning_spaces_rbv2), 7
mlr_tuning_spaces_rtdl, 9

paradox::ParamSet, *10*, *12*
paradox::TuneToken, *3*, *10–12*

R6, *11*
R6::R6Class, *4*

TuningSpace, *3, 4*, *10*, 10